




**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Track system.

**Light Distribution:** Direct

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

**Optical System:** Reflector: Polished aluminium.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium.

**Surface Finish:** Rosewood or powder coated

PB - Polished aluminium reflector | 40 Beam angle

LED	UGR	W	Lm	Lm/W	η(%)	AxbxC(mm)	kg	ORDER CODE
	≤16	25	3566	107	75	Ø108x264x217	1,6	90034.L124.E
	≤16	27	3991	111	75	Ø108x264x217	1,6	90034.L127.E
	≤16	32	4554	108	76	Ø108x264x217	1,6	90034.L133.E

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black


**DETAILS**



Passive cooling

**OPTIONS**

**Colour temperature**



3000K  
Specific colour application (food)

Order code  
**3000**

**CRI**




CRI>90

Order code  
**CRI90**

Example code for order: 90034.L124.E (ORDER CODE) + W (COLOUR/FINISH) + 3000 (OPTIONS)


We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

**Track system**



Option supplied under request.

**PHOTOMETRY**




**FOCUS 32W**  
**PB 4000K 40°**

Mounting height	Average illuminance	Beam diameter
0,5 m	27619 lux	0,33 m
1,0 m	6905 lux	0,66 m
1,5 m	3069 lux	0,99 m
2,0 m	1726 lux	1,32 m
2,5 m	1105 lux	1,64 m
3,0 m	767 lux	1,97 m

**FOCUS 32W**  
**PB 4000K 40°**

**DIMENSIONS**



**TO SPECIFY:**

LED track spotlight. Die cast aluminium body, equipped with the latest LED technology and high performance aluminum reflectors with excellent reflection properties, beam angle of 40°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 3566, 3991 or 4554 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 °C) and passive cooling of the LED through improved heat sink. Optional specific LED colours available for red meat, fresh fish and pastry, CRI>90 and 3000K. Spotlight body rotates 355° and tilts 90° - as Indelague FOCUS.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.