



Norms: EN 60570, EN 60598-1



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface/Suspended or Trimless

Control Gear: Not included.

Materials: Extruded aluminium.

Surface Finish: Anodised in black colour.

Trimless track system



AxBxCxD
3000x23x54x74

f
3000x24

ORDER CODE
926501

Surface mounted or suspended track system




AxBxC
3000x26x54

ORDER CODE
926500


The maximum distance between the driver and the track is 30m.

DIMENSIONS

Trimless track system



Surface mounted or suspended track system



We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Power-supply end piece



HF/DALI
1-10V Left
1-10V Right

Order Code
926540
926541L
926541R

Power-supply connector piece



HF/DALI
1-10V

Order Code
926542
926543

Suspension kit



Suspension kit
•Includes 2 fixing accessories and 2 suspensions.

Order Code
912300

Fixation kit for trimless recessed mounted profile



Fixation kit
• Fixation kit in aluminium.

Order Code
926511

Body connector suspended profile



Body connector
•Body connector in aluminium.

Order Code
926510

Body connector for trimless recessed mounted profile



Body connector
•Body connector in steel.

Order Code
926512

Start Kit



Start Kit - Start / End
• Two end caps included.

Order Code
926520

48V Transformer



75 W power
100 W power
150 W power

Código
965719
965720
965721

Bespoke projects



Option supplied under request.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.