



Norms: EN 60598-1, EN 60598-2-2



d1,0mE

### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED or Halogen (G53) lamp or CDM-R111 (GX8,5) lamp or CDM-T (G12) lamp.

**Control Gear:** Electronic equipment 220-240VAC-50/60Hz. 12V transformer included for G53.

**Materials:** Body: Die cast aluminium.

**Surface Finish:** Powder coated.

LAMP*		W	BEAM ↙	AxB (mm)	⌀	Kg	ORDER CODE
LED 12V	G53	10/15	24/40	Ø174x170	Ø155	1,3	90055.U112.E
HAL 12V	G53	45/60	24/45	Ø174x170	Ø155	1,3	90055.U160.I
CDM-R111	GX8.5	35	10/40	Ø174x175	Ø155	1,3	90055.A135.A
	GX8.5	70	10/40	Ø174x175	Ø155	1,3	90055.A170.A
CDM-T***	G12	35	40	Ø174x170	Ø155	1,3	90055.T135.A
	G12	70	40	Ø174x170	Ø155	1,3	90055.T170.A

Please note: Electronic transformer 35 - 105W (G53). We recommend PHILIPS lamps.


### COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

### OPTIONS

Code	Description
511	Decorative glass**
512	Transparent glass**
513	Opal glass**
--	Lamps as optional.

### DIMENSIONS




\* Lamp not included. | \*\* Option not available for G53 and GX8.5. | \*\*\* For CDM-T (G12), downlight will be supplied with transparent tempered glass as standard.  
Example code for order: 90055.U112.E (ORDER CODE) + W (COLOUR/FINISH)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## PHOTOMETRY

HERA 35W CDM-T G12  
Lamp: 1 x CDM-T 35W



### TO SPECIFY:

Recessed round adjustable downlight with die cast aluminium bezel and aluminium reflector. For ceiling thicknesses of 1-20mm - as Indelague HERA.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.