



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

Mounting: Suspended.

Light Distribution: Direct / Indirect.


Light Source: LED 4000K, CRI>80, 65.000h life time (@L80, B10, Ta 25 C)

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt.

DAM - Microprismatic diffuser | 60% (Direct) + 40% (Indirect)


	LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI
	LED	≤16	39	4748	103	85	1254x250x75	•	•	7,5	9W7K.026.6V.F4	9W7K.026.6V.E4
		≤19	69	9176	113	85	1254x250x75	•	•	8,0	9W7K.047.6V.F4	9W7K.047.6V.E4
		≤19	46	5935	111	86	1534x250x75	•	•	9,0	9W7K.031.6V.F4	9W7K.031.6V.E4
		≤19	83	11470	117	85	1534x250x75	•	•	8,0	9W7K.057.6V.F4	9W7K.057.6V.E4

DOZ - Opal polycarbonate diffuser | 60% (Direct) + 40% (Indirect)

	LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	Kg	HF	DALI
	LED	≤19	39	4748	102	84	1254x250x75	•	•	7,5	9W7K.026.2J.F4	9W7K.026.2J.E4
		≤22	69	9176	110	83	1254x250x75	•	•	8,0	9W7K.047.2J.F4	9W7K.047.2J.E4
		≤22	46	5935	108	84	1534x250x75	•	•	9,0	9W7K.031.2J.F4	9W7K.031.2J.E4
		≤22	83	11470	115	83	1530x250x75	•	•	8,0	9W7K.057.2J.F4	9W7K.057.2J.E4

Please note:
To complete the product a suspension, current supply cable and ceiling rose will be necessary . Please order separately.

DIMENSIONS




Example code for order: 9W7K.057.2J.E4 (DALI) + 3000 + 971700 + 941200 + 910002 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K
Tunable white

Order code
3000
T000


Ceiling rose



Square ceiling rose
Surface mounted
Recessed

Order code
971700
971400


Suspension



Suspension type "I" (x4)

Order code
910002

Light and presence sensor



Option supplied under request.

Current supply cable



1,5 m transparent current cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²
1,5 m transparent current cable 1,5 mm²
3 x 1,5 mm²
5 x 1,5 mm²
7 x 1,5 mm²
9 x 1,5 mm²

Order code
940400
940500
940300
940000
940100
940200

Emergency unit




Emergency unit 3 hours
Emergency unit 1 hour


Order code
K3
K1

• Test function by telecommand signal.

PHOTOMETRY



HERMES D/I 69W
DAM 4000K



HERMES D/I 69W
DOZ 4000K

TO SPECIFY:

Suspended direct/indirect LED luminaire, individually mounted. Available in 2 sizes (1254/1534x250mm) with opal or microprismatic diffuser for light glare control UGR<19, according to EN 12464-1. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, transparent current supply cable, ceiling rose, light and presence sensor and 1 or 3 hours emergency unit. - as Indelague HERMES D/I

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.