



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.


Light Source: LED 4000K, CRI>80, 65.000h life time (@L80, B10, Ta 25 C)

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt.

DAM - Microprismatic diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI	
	LED	≤19	26	3220	97	78	1254x250x55	•	•	6,6	9W7A.026.6V.F4	9W7A.026.6V.E4
		≤22	47	6440	106	77	1254x250x55	•	•	6,6	9W7A.047.6V.F4	9W7A.047.6V.E4
		≤19	31	4025	108	83	1534x250x55	•	•	7,9	9W7A.031.6V.F4	9W7A.031.6V.E4
		≤22	57	8050	109	77	1534x250x55	•	•	7,9	9W7A.057.6V.F4	9W7A.057.6V.E4


DOZ - Opal polycarbonate diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI	
	LED	≤22	26	3220	97	78	1254x250x55	•	•	6,6	9W7A.026.2J.F4	9W7A.026.2J.E4
		≤25	47	6440	106	77	1254x250x55	•	•	6,6	9W7A.047.2J.F4	9W7A.047.2J.E4
		≤22	31	4025	105	81	1534x250x55	•	•	7,9	9W7A.031.2J.F4	9W7A.031.2J.E4
		≤25	57	8050	107	76	1534x250x55	•	•	7,9	9W7A.057.2J.F4	9W7A.057.2J.E4

Please note:

- To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

DIMENSIONS




Example code for order: 9W7A.057.2J.E4 (DALI) + 3000 + 971400 + 940200 + 910002 + K3 (OPTIONS)
 Example code for order: 9W7A.057.2J.E4 (DALI) + 3000 + 971400 + 940200 + 910002 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Colour temperature



3000K
Tunable white

Order code
3000
T000

Light and presence sensor



Option supplied under request.

Ceiling rose



Square ceiling rose
Surface mounted
Recessed

Order code
971700
971400

Current supply cable



1,5 m transparent current cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²
1,5 m transparent current cable 1,5 mm²
3 x 1,5 mm²
5 x 1,5 mm²
7 x 1,5 mm²
9 x 1,5 mm²

Order code
940400
940500
940300
940000
940100
940200

Suspension



Suspension type "I" (x4)

Order code
910002

Emergency unit




Emergency unit 3 hours
Emergency unit 1 hour


Order code
K3
K1

• Test function by telecommand signal.

PHOTOMETRY



HERMES 26W
DAM 4000K



HERMES 26W
DOZ 4000K

TO SPECIFY:

Suspended LED luminaire, individually mounted. Available in 2 sizes (1254/1534x250mm) with opal or microprismatic diffuser for light glare control UGR<19. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, transparent current supply cable, ceiling rose, light and presence sensor and 1 or 3 hours emergency unit. - as Indelague HERMES

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.