



**LED**

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** Direct / Indirect.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 °C).


**Optical System:** Optical glass convex lenses.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.


**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

#### 50 Lens

	LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	LED	≤10	57	7900	114	82	600x600x46	8,3	90385.L038.E5	90385.L038.H5
		≤10	53	7367	111	80	1180x258x46	7,6	90386.L038.E5	90386.L038.H5

#### 80 Lens


	LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	LED	≤13	57	7900	114	82	600x600x46	8,3	90385.L038.E8	90385.L038.H8
		≤13	53	7367	111	80	1180x258x46	7,6	90386.L038.E8	90386.L038.H8

Please note:

- To complete the 600x600 version add suspension, current supply cable and ceiling rose. Please order separately.
- To complete the 1180x258 version add suspension, please order separately. Current supply cable and ceiling rose included.

### COLOUR / FINISH

Code	Description
 W/B	(1) White / (2) Black
 W/G	(1) White / (2) Grey
 G/W	(1) Grey / (2) White
 G/B	(1) Grey / (2) Black
 B/W	(1) Black / (2) White
 B/G	(1) Black / (2) Grey



Subtitle:  
 (1) Luminaire outside trim colour  
 (2) Luminaire inside trim colour


- The finish order code is based on two colours, where (1) is the luminaire outside trim colour and (2) is the luminaire inside trim colour.

Example code for order: 90385.L038.H8 (DALI) + W/B (COLOUR/FINISH) + 3000 + CXS + 940500 + 910001 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature



3000K

Order code  
**3000**

#### Bluetooth module



Bluetooth module for wireless control through smartphone.

Option supplied under request.

#### Ceiling rose (for 600x600mm version)



Square ceiling rose  
Surface mounted  
Recessed

- Please order suspension type "I" (x4) separately.
- Other colours under request.

Order code

**9717**  
**9714**

#### Ceiling rose (for 1180x258mm version)




Rectangular ceiling rose  
Surface mounted  
Recessed

- Please order suspension type "I" (x2) separately.
- Other colours under request.

Order code

**CXS**  
**CXE**

#### Current supply cable



1,5m transparent cable 0,75mm2  
3x0,75mm2  
5x0,75mm2

Order code

**940400**  
**940500**

#### Suspension



Suspension type "I" (x2)  
Suspension type "I" (x4)

- (x2) only for 1180x258 version
- (x4) only for 600x600 version

Order code

**910001**


**910002**

#### Low power version




Option supplied under request.

### PHOTOMETRY




**HIKARI D/I 57W**  
**(600x600mm) 4000K 80°**



**HIKARI D/I 57W**  
**(600x600mm) 4000K 50°**

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

DIMENSIONS



TO SPECIFY:

Suspended direct/indirect LED luminaire, with modern and elegant lines. Equipped with 50 or 80 convex optical glass lenses, providing high visual comfort ( $UGR \leq 10$ ). Standard version with 4000K,  $CRI > 80$  and 50.000h lifetime (@ L80, B10, Ta 25 C). Different colour combinations available. Optional DALI dimmable driver, 3000K and Bluetooth module for wireless control through smartphone. Suspension, current supply cable and ceiling rose as accessories. - as Roxo Lighting HIKARI D/I

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.