

LED



Norms: EN 60598-1, EN 60598-2-2



IP 20



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

BLINE - Opal polycarbonate diffuser


LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	■	Kg	HF	DALI
	1x13	2000	370	35	94	76	225x225x114	202x205	1,42	90296.L113.E	90296.L113.H
	1x17	2600	485	36	96	75	225x225x114	202x205	1,42	90296.L117.E	90296.L117.H
	1x19	3000	550	35	-	-	225x225x114	202x205	1,42	90296.L119.E	90296.L119.H

DAM - Microprismatic diffuser

LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	■	Kg	HF	DALI
	1x13	2000	370	35	88	71	225x225x114	202x205	1,42	90265.L113.E	90265.L113.H
	1x17	2600	485	36	88	68	225x225x114	202x205	1,42	90265.L117.E	90265.L117.H
	1x19	3000	550	35	-	-	225x225x114	202x205	1,42	90265.L119.E	90265.L119.H


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
K	Red (RAL 3020)
T	Yellow (RAL 1021)
U	Blue (RAL 5002)
V	Green (RAL 6018)
G	Grey (RAL 9006)
R	Rust



Legend:
 (1) Exterior painting (frame)
 (2) Interior painting (reflector)
 Example:
 (1) B + (2) W

DIMENSIONS



Note:

To order the complete product, indicate the ordering code of the frame more the reflector code and finally the two codes for the color.

First exterior paint (frame), followed by the interior paint (reflector) (see order example).


* Led included.

Example code for order: 90296.L119.H (DALI) + (1) B + (2) W (COLOUR / FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature




3000K


Order code
3000

PHOTOMETRY

HOLI SQ Grand 17W BLINE
LED



HOLI SQ Grand 17W DAM
LED



TO SPECIFY:

Square ceiling recessed LED downlight, with frame, 225x225mm, with a maximum height of 114mm. Painted in epoxy polyester, with the possibility of multiple colour combinations between the frame and the reflector. Luminous flux of 2000lm, 2600lm or 3000lm and with opal polycarbonate diffuser (BLINE). Optional with microprismatic diffuser and in 3000K. To install in ceilings with thickness between 1 and 20mm – as Indelague HOLI Sq Grand.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.