



LED

Norms: EN 60598-1, EN 60598-2-2



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

LIGHT+ - Opal diffuser

LAMP	W	Lm	mA	V	Lm/W	l(%)	AxBxC (mm)	DxE (mm)	█	Kg	HF	DALI
LED	9	1035	190	35	84	73	106x106x74	180x180	114x114	0,7	90272.L106.E	90272.L106.H
	12	1469	280	36	91	74	106x106x74	180x180	114x114	0,7	90272.L110.E	90272.L110.H

PRISM+ - Microprismatic diffuser

LAMP	W	Lm	mA	V	Lm/W	l(%)	AxBxC (mm)	DxE (mm)	█	Kg	HF	DALI
LED	9	1035	190	35	78	68	106x106x74	180x180	114x114	0,7	90223.L106.E	90223.L106.H
	12	1469	280	36	84	69	106x106x74	180x180	114x114	0,7	90223.L110.E	90223.L110.H

Please note: To complete the product add mounting kit. Please order separately.

**COLOUR / FINISH**

Code	Description
□□	W/W (1) White / (2) White
□■	W/G (1) White / (2) Grey
□■	W/B (1) White / (2) Black
□■	W/D (1) White / (2) Golden Eye
■□	B/W (1) Black / (2) White
■■	B/G (1) Black / (2) Grey
■■	B/B (1) Black / (2) Black
■■	B/D (1) Black / (2) Golden Eye



Subtitle:  
(1) Mounting kit colour finish  
(2) Reflector colour finish  
  
• The finish order code is based on two colours, where (1) is the mounting kit colour finish and (2) is the reflector colour finish.

Example code for order: 90267.L106.H (DALI) + B/W + (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

**Colour temperature**

Order code  
**3000**

3000K



**Mounting kit**

Order code  
**971501**

Mounting kit trimless



**Safety cable**


Order code  
**955000**

Steel safety cable




**Emergency unit**

Option supplied under request.



**DIMENSIONS**



**Mounting kit**



**TO SPECIFY:**

Square LED recessed trimless downlight. Maximum high of 74mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1035 or 1469 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq /T

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.