



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).


Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser



LAMP	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	DxE (mm)		Kg	HF	DALI
LED	15	1992	370	35	106	80	190x190x90	272x272	200x200	1,5	90288.L113.E	90288.L113.H
	20	2535	485	36	101	80	190x190x90	272x272	200x200	1,5	90288.L117.E	90288.L117.H
	23	2988	550	35	105	81	190x190x90	272x272	200x200	1,5	90288.L119.E	90288.L119.H

PRISM+ - Microprismatic diffuser




LAMP	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	DxE (mm)		Kg	HF	DALI
LED	15	1992	370	35	98	74	190x190x90	272x272	200x200	1,5	90225.L113.E	90225.L113.H
	20	2535	485	36	93	73	190x190x90	272x272	200x200	1,5	90225.L117.E	90225.L117.H
	23	2988	550	35	96	74	190x190x90	272x272	200x200	1,5	90225.L119.E	90225.L119.H

Please note: To complete the product add mounting kit. Please order separately.

COLOUR / FINISH

Code	Description
W/W	(1) White / (2) White
W/G	(1) White / (2) Grey
W/B	(1) White / (2) Black
W/D	(1) White / (2) Golden Eye
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey
B/B	(1) Black / (2) Black
B/D	(1) Black / (2) Golden Eye



Subtitle:

- (1) Mounting kit colour finish
- (2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the mounting kit colour finish and (2) is the reflector colour finish.

Example code for order: 90288.L113.H (DALI) + B/W + (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Mounting kit



Mounting kit trimless

Order code
971503


Safety cable



Steel safety cable



Order code
955000

Emergency unit



Option supplied under request.

DIMENSIONS



TO SPECIFY:

Square LED recessed trimless downlight. Maximum high of 90mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1992, 2535 or 2988 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Roxo Lighting HOLI Sq /T Grand