



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

Fixing system: Mounting kit trimless.

LIGHT+ - Opal diffuser

LAMP	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	DxE (mm)		Kg	HF	DALI
LED	9	1035	190	35	84	73	95x95x71	153x153	100x101	0,6	90267.L106.E	90267.L106.H

PRISM+ - Difusor microprismático

LAMP	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	DxE (mm)		Kg	HF	DALI
LED	9	1035	190	35	78	68	95x95x71	153x153	100x101	0,6	90222.L106.E	90222.L106.H

Please note: To complete the product add mounting kit. Please order separately.

COLOUR / FINISH

Code	Description
W/B	(1) White/ (2) White
W/G	(1) White / (2) Grey
W/B	(1) White / (2) Black
W/D	(1) White / (2) Golden Eye
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey
B/B	(1) Black / (2) Black
B/D	(1) Black / (2) Golden Eye



Subtitle:
 (1) Mounting kit colour finish
 (2) Reflector colour finish
 • The finish order code is based on two colours, where (1) is the mounting kit colour finish and (2) is the reflector colour finish.

Example code for order: 90267.L106.H (DALI) + B/W + (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code
3000

3000K



Safety cable

Order code
955000

Steel safety cable



Emergency unit

Option supplied under request.




Mounting kit

Order code
971500

Mounting kit trimless



DIMENSIONS



TO SPECIFY:

Square LED recessed trimless downlight. Maximum high of 71mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1035 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Roxo Lighting HOLI Sq /T Mini

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.