



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and business areas, public buildings, housing, offices, hotel and restaurant services, art and culture spaces, corridors.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 60.000h life (@L70, B10, Ta 25 C).


Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.









Materials: Body: Steel sheet.


Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	10	974	96	99	150x150x130	1,6	90270.L106.E	90270.L106.H
	14	1428	101	99	150x150x130	1,6	90270.L110.E	90270.L110.H

COLOUR / FINISH


Code	Description
 W/W	(1) White / (2) White
 W/G	(1) White / (2) Grey
 W/B	(1) White / (2) Black
 W/D	(1) White / (2) Golden Eye
 B/W	(1) Black / (2) White
 B/G	(1) Black / (2) Grey
 B/B	(1) Black / (2) Black
 B/D	(1) Black / (2) Golden Eye



Subtitle:
 (1) Body colour finish
 (2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the reflector colour finish.

DIMENSIONS



Example code for order: 90270.L110.H (DALI) + W/W (COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Colour temperature

Order code
3000

3000K



PHOTOMETRY



HOLI Sq /C 14W
LIGHT+ 4000K

TO SPECIFY:

Square LED surface downlight. Maximum high of 130mm and opal Light+ polycarbonate diffuser. Standard total luminous flux of 974 or 1428 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Roxo Lighting HOLI Sq /C

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.