



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 60.000h life (@L70, B10, Ta 25 C).


Optical System: Diffuser: Opal

Control Gear: LED driver, 220-240VAC-50/60Hz.









Materials: Body: Steel sheet.


Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	19	1951	102	99	225x225x130	2,6	90292.L113.E	90292.L113.H
	24	2468	102	99	225x225x130	2,6	90292.L117.E	90292.L117.H
	27	2928	107	99	225x225x130	2,6	90292.L119.E	90292.L119.H

COLOUR / FINISH


Code	Description
 W/W	(1) White / (2) White
 W/G	(1) White / (2) Grey
 W/B	(1) White / (2) Black
 W/D	(1) White / (2) Golden Eye
 B/W	(1) Black / (2) White
 B/G	(1) Black / (2) Grey
 B/B	(1) Black / (2) Black
 B/D	(1) Black / (2) Golden Eye



Subtitle:
(1) Body colour finish
(2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the reflector colour finish.

DIMENSIONS



Example code for order: 90292.L113.H (DALI) + W/W (COLOUR/FINISH) + 3000

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.


OPTIONS

Colour temperature


Order code

3000K

3000



PHOTOMETRY



HOLI Sq /C Grand 27W
LIGHT+ 4000K

TO SPECIFY:

Square LED surface downlight. Maximum high of 130mm and opal Light+ polycarbonate diffuser. Standard total luminous flux of 1951, 2468 or 2928 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq /C Grand.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.