



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 60.000h life (@L70, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	10	974	96	99	115x115x120	1,0	90269.L106.E	90269.L106.H

COLOUR / FINISH


Code	Description
W/W	(1) White / (2) White
W/G	(1) White / (2) Grey
W/B	(1) White / (2) Black
W/D	(1) White / (2) Golden Eye
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey
B/B	(1) Black / (2) Black
B/D	(1) Black / (2) Golden Eye



Subtitle:
(1) Body colour finish
(2) Reflector colour finish


• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the reflector colour finish.

DIMENSIONS



OPTIONS

Colour temperature




3000K

Order code
3000

Example code for order: 90269.L106.H (DALI) + B/B (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



HOLI Sq /C Mini 10W
LIGHT+ 4000K

TO SPECIFY:

Square LED surface downlight. Maximum high of 120mm and opal Light+ polycarbonate diffuser. Standard total luminous flux of 974 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq /C Mini.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.