



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	■	Kg	HF	DALI
	9	1035	190	34	83	72	135x135x73	115x115	0,8	90294.L106.E	90294.L106.H
	12	1469	280	35	87	71	135x135x73	115x115	0,8	90294.L110.E	90294.L110.H

PRISM+ - Microprismatic diffuser

LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)	■	Kg	HF	DALI
	9	1035	190	34	78	68	135x135x73	115x115	0,8	90259.L106.E	90259.L106.H
	12	1469	280	35	84	69	135x135x73	115x115	0,8	90259.L110.E	90259.L110.H

COLOUR / FINISH


Code	Description
W/W	(1) White / (2) White
W/G	(1) White / (2) Grey
W/B	(1) White / (2) Black
W/D	(1) White / (2) Golden Eye
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey
B/B	(1) Black / (2) Black
B/D	(1) Black / (2) Golden Eye



Subtitle:
(1) Trim colour finish
(2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the trim colour finish and (2) is the reflector colour finish.

DIMENSIONS



Example code for order: 90294.L106.H (DALI) + W/W (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000


Safety cable



Steel safety cable


Order code
955000

Emergency unit




Option supplied under request.

PHOTOMETRY



**HOLI Sq 12W
LIGHT+ 4000K**



**HOLI Sq 12W
PRISM+ 4000K**

TO SPECIFY:

Square LED recessed downlight. Maximum high of 73mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1035 or 1469 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.