



**LED**

Norms: EN 60598-1, EN 60598-2-2



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

**Optical System:** Diffuser: Opal polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

#### LIGHT+ - Opal diffuser


LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)		Kg	HF	DALI
	15	1992	370	35	105	79	225x225x89	207x207	1,6	90296.L113.E	90296.L113.H
	20	2535	485	36	100	79	225x225x89	207x207	1,6	90296.L117.E	90296.L117.H
	23	2988	550	35	104	80	225x225x89	207x207	1,6	90296.L119.E	90296.L119.H

#### PRISM+ - Microprismatic diffuser

LED	W	Lm	mA	V	Lm/W	η(%)	AxBxC (mm)		Kg	HF	DALI
	15	1992	370	35	100	75	225x225x89	207x207	1,6	90265.L113.E	90265.L113.H
	20	2535	485	36	93	73	225x225x89	207x207	1,6	90265.L117.E	90265.L117.H
	23	2988	550	35	97	75	225x225x89	207x207	1,6	90265.L119.E	90265.L119.H

#### COLOUR / FINISH


Code	Description
W/W	(1) White / (2) White
W/G	(1) White / (2) Grey
W/B	(1) White / (2) Black
W/D	(1) White / (2) Golden Eye
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey
B/B	(1) Black / (2) Black
B/D	(1) Black / (2) Golden Eye



Subtitle:  
(1) Trim colour finish  
(2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the trim colour finish and (2) is the reflector colour finish.

#### DIMENSIONS



Example code for order: 90296.L119.H (DALI) + W/W (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature



3000K

Order code  
**3000**


#### Steel safety cable



Steel safety cable


Order code  
**955000**

#### Emergency unit




Option supplied under request.

### PHOTOMETRY



**HOLI Sq Grand 23W  
LIGHT+ 4000K**



**HOLI Sq Grand 23W  
PRISM+ 4000K**

#### TO SPECIFY:

Square LED recessed downlight. Maximum high of 89mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1992, 2535 or 2988 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq Grand

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.