



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Light Distribution: Direct

Light Source: LED 4000K, CRI>80, 60.000h life (@L70, B10, Ta 25 C).



Optical System: Diffuser: Microprismatic or Opal

Control Gear: LED driver, 220-240VAC-50/60Hz.



Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

	LED	W	Lm	Lm/W	η (%)	AxBxC	DxExF		kg	HF	DALI
		12	1469	98	80	147x147x80	222x222x32	155x155	1,2	90289.L110.E	90289.L110.H
		15	1992	102	77	147x147x80	222x222x32	155x155	1,2	90289.L113.E	90289.L113.H
		20	2535	96	76	147x147x80	222x222x32	155x155	1,2	90289.L117.E	90289.L117.H









PRISM+ - Microprismatic diffuser

	LED	W	Lm	Lm/W	η (%)	AxBxC	DxExF		kg	HF	DALI
		12	1469	89	73	147x147x80	222x222x32	155x155	1,2	90289.L110.E	90289.L110.H
		15	1992	97	73	147x147x80	222x222x32	155x155	1,2	90289.L113.E	90289.L113.H
		20	2535	93	73	147x147x80	222x222x32	155x155	1,2	90228.L117.E	90228.L117.H

LIGHT+ | PRISM+

• To complete the product add mounting kit. Please order separately.

COLOUR / FINISH

Code	Description
 W/W	(1) White / (2) White
 W/G	(1) White / (2) Grey
 W/B	(1) White / (2) Black
 W/D	(1) White / (2) Golden Eye
 B/W	(1) Black / (2) White
 B/G	(1) Black / (2) Grey
 B/B	(1) Black / (2) Black
 B/D	(1) Black / (2) Golden Eye



Subtitle:

(1) Mounting kit colour finish
(2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the mounting kit colour finish and (2) is the reflector colour finish.

Example code for order: 90289.L110.H (DALI) + W/W (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Mounting kit



Mounting kit trimless

Order code
971502


Safety cable



Steel safety cable



Order code
955000

Emergency unit



Option supplied under request.

DIMENSIONS



TO SPECIFY:

Square LED semi-recessed downlight. Maximum high of 80mm with visible 32mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1469, 1992 or 2535 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq /SR Max.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.