



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 60.000h life (@L70, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LAMP	W	lm	mA	Vdc	lm/W	η(%)	AxBxC (mm)	DxExF (mm)	█	kg	HF	DALI
LED	9	1035	190	35	84	73	95x95x73	153x153x32	101x101	0,7	90271.L106.E	90271.L106.H

PRISM+ - Microprismatic diffuser

LAMP	W	lm	mA	Vdc	lm/W	η(%)	AxBxC (mm)	DxExF (mm)	█	kg	HF	DALI
LED	9	1035	190	35	78	68	95x95x73	153x153x32	101x101	0,7	90226.L106.E	90271.L106.H

Please note:
• To complete the product add mounting kit. Please order separately.

COLOUR / FINISH

Code	Description
□□	W/W (1) White / (2) White
□■	W/G (1) White / (2) Grey
□■	W/B (1) White / (2) Black
□■	W/D (1) White / (2) Golden Eye
■□	B/W (1) Black / (2) White
■■	B/G (1) Black / (2) Grey
■■	B/B (1) Black / (2) Black
■■	B/D (1) Black / (2) Golden Eye



Subtitle:
(1) Mounting kit colour finish
(2) Reflector colour finish

• The finish order code is based on two colours, where (1) is the mounting kit colour finish and (2) is the reflector colour finish.

Example code for order: 90271.L106.H (DALI) + W/W (COLOUR/FINISH) + 3000 + 972300 (OPTIONS)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code
3000

3000K



Mounting kit

Code
972300

Mounting kit semi-recessed



Safety cable

Order code
955000

Steel safety cable




Emergency unit

Option supplied under request.



DIMENSIONS



TO SPECIFY:

Square LED semi-recessed downlight. Maximum high of 73mm with visible 32mm and high glare control polycarbonate diffuser LIGHT+ or PRISM+. Standard total luminous flux of 1035 lm, 4000K, CRI>80 and 60.000h lifetime (@ L70, B10, Ta 25 C) and integral heat sink to provide optimum heat dissipation. Optional DALI dimmable driver and 3000K. Multiple colour configurations available. - as Indelague HOLI Sq /SR Mini

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.