

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Industrial areas, commercial areas.

Mounting: Surface/Wall Mounted.


Light Distribution: Direct.

Control Gear: Electronic equipment
220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt (RAL9016).


ACW - Steel sheet wide beam symmetric reflector

	LAMP*	W	AxBxC (mm)	B1xC1 (mm)	K1	K3	Kg	HF	DSI	DALI
	T5	1x28	1184x128x64	-	•	-	1,8	9G1T.128.04.A4	9G1T.128.04.84	9G1T.128.04.74
		1x35	1484x128x64	-	•	•	2	9G1T.135.04.A4	9G1T.135.04.84	9G1T.135.04.74
		1x49	1484x128x64	-	•	•	2	9G1T.149.04.A4	9G1T.149.04.84	9G1T.149.04.74
		1x54	1184x128x64	-	•	-	1,8	9G1T.154.04.A4	9G1T.154.04.84	9G1T.154.04.74
		1x80	1484x128x64	-	•	•	2	9G1T.180.04.A4	9G1T.180.04.84	9G1T.180.04.74
		2x28	-	128x64	-	-	2	9G1T.228.04.A4	9G1T.228.04.84	9G1T.228.04.74
		2x35	-	128x64	•	•	2,2	9G1T.235.04.A4	9G1T.235.04.84	9G1T.235.04.74
		2x49	-	128x64	•	•	2,2	9G1T.249.04.A4	9G1T.249.04.84	9G1T.249.04.74
		2x54	-	128x64	-	-	2	9G1T.254.04.A4	9G1T.254.04.84	9G1T.254.04.74
		2x80	-	128x64	•	•	2,2	9G1T.280.04.A4	9G1T.280.04.84	9G1T.280.04.74
	T8	1x36	1233x171x80	-	•	•	2,2	9D59.136.04.A4	9D59.136.04.84	9D59.136.04.74
		1x58	1533x171x80	-	•	•	2,4	9D59.158.04.A4	9D59.158.04.84	9D59.158.04.74
		2x36	-	219x80	•	•	2,5	9D59.236.04.A4	9D59.236.04.84	9D59.236.04.74
		2x58	-	219x80	•	•	3,2	9D59.258.04.A4	9D59.258.04.84	9D59.258.04.74


* Lamp not included.
Example code for order: 9D59.258.04.A4 (HF) + W3M + P/LED (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.


ECW - Aluminium wide beam symmetric reflector

 LAMP*	W	AxBxC (mm)	B1xC1 (mm)	K1	K3	Kg	HF	DSI	DALI	
T5	1x28	1184x128x64	-	•	-	1,3	9G1T.128.41.A4	9G1T.128.41.84	9G1T.128.41.74	
	1x35	1484x128x64	-	•	•	1,5	9G1T.135.41.A4	9G1T.135.41.84	9G1T.135.41.74	
	1x49	1484x128x64	-	•	•	1,5	9G1T.149.41.A4	9G1T.149.41.84	9G1T.149.41.74	
	1x54	1184x128x64	-	•	-	1,3	9G1T.154.41.A4	9G1T.154.41.84	9G1T.154.41.74	
	1x80	1484x128x64	-	•	•	1,5	9G1T.180.41.A4	9G1T.180.41.84	9G1T.180.41.74	
	2x28	-	128x64	-	-	1,4	9G1T.228.41.A4	9G1T.228.41.84	9G1T.228.41.74	
	2x35	-	128x64	•	•	1,6	9G1T.235.41.A4	9G1T.235.41.84	9G1T.235.41.74	
	2x49	-	128x64	•	•	1,6	9G1T.249.41.A4	9G1T.249.41.84	9G1T.249.41.74	
	2x54	-	128x64	-	-	1,4	9G1T.254.41.A4	9G1T.254.41.84	9G1T.254.41.74	
	2x80	-	128x64	•	•	1,6	9G1T.280.41.A4	9G1T.280.41.84	9G1T.280.41.74	
	T8	1x36	1233x171x80	-	•	•	1,6	9D59.136.41.A4	9D59.136.41.84	9D59.136.41.74
		1x58	1533x171x80	-	•	•	1,8	9D59.158.41.A4	9D59.158.41.84	9D59.158.41.74
		2x36	-	219x80	•	•	1,9	9D59.236.41.A4	9D59.236.41.84	9D59.236.41.74
		2x58	-	219x80	•	•	2,6	9D59.258.41.A4	9D59.258.41.84	9D59.258.41.74

NL0 - Curved symmetric reflector, made from aluminium


 LAMP*	W	AxBxC (mm)	B1xC1 (mm)	K1	K3	Kg	HF	DSI	DALI	
T5	1x28	1184x108x77	-	•	-	2,1	9G1T.128.73.A4	9G1T.128.73.84	9G1T.128.73.74	
	1x35	1484x108x77	-	•	•	2,3	9G1T.135.73.A4	9G1T.135.73.84	9G1T.135.73.74	
	1x49	1484x108x77	-	•	•	2,3	9G1T.149.73.A4	9G1T.149.73.84	9G1T.149.73.74	
	1x54	1184x108x77	-	•	-	2,1	9G1T.154.73.A4	9G1T.154.73.84	9G1T.154.73.74	
	1x80	1484x108x77	-	•	•	2,3	9G1T.180.73.A4	9G1T.180.73.84	9G1T.180.73.74	
	2x28	-	108x77	-	-	2,2	9G1T.228.73.A4	9G1T.228.73.84	9G1T.228.73.74	
	2x35	-	108x77	•	•	2,4	9G1T.235.73.A4	9G1T.235.73.84	9G1T.235.73.74	
	2x49	-	108x77	•	•	2,4	9G1T.249.73.A4	9G1T.249.73.84	9G1T.249.73.74	
	2x54	-	108x77	-	-	2,2	9G1T.254.73.A4	9G1T.254.73.84	9G1T.254.73.74	
	2x80	-	108x77	•	•	2,4	9G1T.280.73.A4	9G1T.280.73.84	9G1T.280.73.74	
	T8	1x36	1233x220x128	-	•	•	2,3	9D59.136.73.A4	9D59.136.73.84	9D59.136.73.74
		1x58	1533x220x128	-	•	•	2,5	9D59.158.73.A4	9D59.158.73.84	9D59.158.73.74
		2x36	-	220x128	•	•	2,6	9D59.236.73.A4	9D59.236.73.84	9D59.236.73.74
		2x58	-	220x128	•	•	3,3	9D59.258.73.A4	9D59.258.73.84	9D59.258.73.74

MA0 - Steel sheet asymmetric reflector

 LAMP*	W	AxBxC (mm)	B1xC1 (mm)	K1	K3	Kg	HF	DSI	DALI	
T5	1x28	1184x87x64	-	•	-	1,6	9G1T.128.59.A4	9G1T.128.59.84	9G1T.128.59.74	
	1x35	1484x87x64	-	•	•	1,8	9G1T.135.59.A4	9G1T.135.59.84	9G1T.135.59.74	
	1x49	1484x87x64	-	•	•	1,8	9G1T.149.59.A4	9G1T.149.59.84	9G1T.149.59.74	
	1x54	1184x87x64	-	•	-	1,6	9G1T.154.59.A4	9G1T.154.59.84	9G1T.154.59.74	
	1x80	1484x87x64	-	•	•	1,8	9G1T.180.59.A4	9G1T.180.59.84	9G1T.180.59.74	
	2x28	-	97x64	-	-	1,8	9G1T.228.59.A4	9G1T.228.59.84	9G1T.228.59.74	
	2x35	-	97x64	•	•	2	9G1T.235.59.A4	9G1T.235.59.84	9G1T.235.59.74	
	2x49	-	97x64	•	•	2	9G1T.249.59.A4	9G1T.249.59.84	9G1T.249.59.74	
	2x54	-	97x64	-	-	1,8	9G1T.254.59.A4	9G1T.254.59.84	9G1T.254.59.74	
	2x80	-	97x64	•	•	2	9G1T.280.59.A4	9G1T.280.59.84	9G1T.280.59.74	
	T8	1x36	1233x116x84	-	•	•	2	9D59.136.59.A4	9D59.136.59.84	9D59.136.59.74
		1x58	1533x116x84	-	•	•	2,2	9D59.158.59.A4	9D59.158.59.84	9D59.158.59.74
		2x36	-	172x84	•	•	2,3	9D59.236.59.A4	9D59.236.59.84	9D59.236.59.74
		2x58	-	172x84	•	•	3	9D59.258.59.A4	9D59.258.59.84	9D59.258.59.74

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

DRM - Deep curved hammered aluminium reflector


LAMP*	W	AxBxC (mm)	B1xC1 (mm)	K1	K3	Kg	HF	DSI	DALI	
	T5	1x28	1184x222x157	-	•	-	2,3	9G1T.128.28.A4	9G1T.128.28.84	9G1T.128.28.74
		1x35	1484x222x157	-	•	•	2,5	9G1T.135.28.A4	9G1T.135.28.84	9G1T.135.28.74
		1x49	1484x222x157	-	•	•	2,5	9G1T.149.28.A4	9G1T.149.28.84	9G1T.149.28.74
		1x54	1184x222x157	-	•	-	2,3	9G1T.154.28.A4	9G1T.154.28.84	9G1T.154.28.74
		1x80	1484x222x157	-	•	•	2,5	9G1T.180.28.A4	9G1T.180.28.84	9G1T.180.28.74
		2x28	-	253x157	-	-	2,4	9G1T.228.28.A4	9G1T.228.28.84	9G1T.228.28.74
		2x35	-	253x157	•	•	2,6	9G1T.235.28.A4	9G1T.235.28.84	9G1T.235.28.74
		2x49	-	253x157	•	•	2,6	9G1T.249.28.A4	9G1T.249.28.84	9G1T.249.28.74
		2x54	-	253x157	-	-	2,4	9G1T.254.28.A4	9G1T.254.28.84	9G1T.254.28.74
		2x80	-	253x157	•	•	2,6	9G1T.280.28.A4	9G1T.280.28.84	9G1T.280.28.74

OPTIONS


Code	Description
W3M	Connector 3-pole wieland GST 18i3 male.
W5M	Connector 5-pole wieland GST 18i5 male.
W5MD	Connector 5-pole wieland GST 18i5 DIM male.
W3MFC	Connector 3-pole wieland GST 18i3 male + 1m cable with 3-pole wieland GST 18i3 female.
W5MFC	Connector 5-pole wieland GST 18i5 male + 1m cable with 5-pole wieland GST 18i5 female.
W5MFC	Connector 5-pole wieland GST 18i5 DIM male + 1m cable with 5-pole wieland GST 18i5 DIM female.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
P/LED	Electrification for LED lamp (T8).
--	Lamps as optional.

PHOTOMETRY

IAI 1x58W ECW
Lamp: 1 x 58W/840




IAI 2x36W NLO
Lamp: 2 x 36W/840




We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

DIMENSIONS


IAIT5 (Body)




ACW/ECW




NL0




MA0




DRM




IAIT8 (Body)




ACW/ECW



NL0



MA0



TO SPECIFY:

Single or twin batten for 28/35/49/54/80W T5(G5) or 36/58W T8(G13) fluorescent lamps. Optional symmetric or asymmetric reflectors, connectors, dimmable version and 1 or 3 hours emergency available – as Indelague IAI.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.