



Norms: EN 60598-1, EN 60598-2-2



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** TC-DEL (G24q-2/G24q-3) lamp or TC-TEL (GX24q-3) lamp.

**Optical System:** Diffuser: Transparent tempered glass.

**Control Gear:** Electronic equipment 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

PB - Polished aluminium reflector | 80 Beam angle

| LAMP*  | UGR |         | W    | η(%) | AxBxC (mm)  |         | Kg   | HF           | DSI          | DALI         |
|--------|-----|---------|------|------|-------------|---------|------|--------------|--------------|--------------|
| TC-DEL | ≤22 | G24q-2  | 1x18 | 70   | 225x225x110 | 207x207 | 1,34 | 90118.E118.A | 90118.E118.C | 90118.E118.D |
|        | ≤22 | G24q-3  | 1x26 | 64   | 225x225x110 | 207x207 | 1,34 | 90118.F126.A | 90118.F126.C | 90118.F126.D |
|        | ≤22 | G24q-2  | 2x18 | 61   | 225x225x110 | 207x207 | 1,39 | 90118.E218.A | 90118.E218.C | 90118.E218.D |
|        | ≤22 | G24q-3  | 2x26 | 45   | 225x225x110 | 207x207 | 1,39 | 90118.F226.A | 90118.F226.C | 90118.F226.D |
| TC-TEL | ≤22 | GX24q-3 | 1x26 | 64   | 225x225x110 | 207x207 | 1,34 | 90118.I126.A | 90118.I126.C | 90118.I126.D |
|        | ≤22 | GX24q-3 | 1x32 | 59   | 225x225x110 | 207x207 | 1,34 | 90118.I132.A | 90118.I132.C | 90118.I132.D |
|        | ≤25 | GX24q-3 | 2x26 | 58   | 225x225x110 | 207x207 | 1,39 | 90118.I226.A | 90118.I226.C | 90118.I226.D |
|        | ≤22 | GX24q-3 | 2x32 | 45   | 225x225x110 | 207x207 | 1,39 | 90118.I232.A | 90118.I232.C | 90118.I232.D |


### COLOUR / FINISH

| Code | Description      |
|------|------------------|
| W    | White (RAL 9016) |
| B    | Black (RAL 9005) |
| G    | Grey (RAL 9006)  |

### OPTIONS

| Code | Description             |
|------|-------------------------|
| 003  | Opal glass.             |
| K3   | Emergency unit 3 hours. |
| K1   | Emergency unit 1 hour.  |
| --   | Lamps as optional.      |

### DETAILS



Easy to change lamps

\* Lamp not included.


Example code for order: 90118.F226.D (DALI) + W (COLOUR/FINISH) + 003 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.



### PHOTOMETRY

### DIMENSIONS

**JUKE /G 1x26W PB**  
Lamp: 1 x TC-TEL 26W/640



**JUKE /G 2x18W PB**  
Lamp: 2 x TC-DEL 18W/840



### TO SPECIFY:

Recessed IP54 single/twin lamp 18/26W TC-DEL or 26/32W TC-TEL compact fluorescent downlight, with steel sheet body and aluminium reflector. Optional opal 4mm tempered glass and 1 or 3 hours emergency available. For ceiling thicknesses of 1-25mm – as Roxo Lighting JUKE /G.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.