



LED



Norms: EN 60598-1



IP 40



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Desk.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: Pre-wired with 1,5m H05VV-F cable with electric socket "type F".

Materials: Body: Extruded aluminium.


Surface Finish: Powder coated.

DOZ - Opal polycarbonate diffuser

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	SwitchDIM
LED	8	854	75	70	170x478x504	2,2	90275.L106.E	90275.L106.F

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
W/G	(1) White / (2) Grey
G/W	(1) Grey / (2) White
G/B	(1) Grey / (2) Black
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey



Subtitle:
(1) Body colour finish
(2) Luminaire base colour finish


• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the luminaire base colour finish.

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000

USB connection



USB connection

Code
USB

Example code for order: 90275.L106.E (HF) + W/B (COLOUR/FINISH) + 3000 + USB (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

DETAILS




Touchless ON/OFF control sensor and USB connection detail



SwitchDIM button

PHOTOMETRY



KANTO /D 8W
DOZ 4000K

TO SPECIFY:

Modern design LED desk luminaire. Extruded aluminium body, powder coated in epoxy polyester and high glare control diffuser (UGR<19). Standard total luminous flux of 854 lm, 4000K, CRI>80 and 50.000h lifetime(@L80, B10, Ta 25 C). Standard version with Touchless ON/OFF control sensor, ergonomically integrated into the luminaire stand and electric socket type F with 1.5m H05VV-F cable included. Flat steel base capable of 355° rotation. Optional integral USB charging device, 3000K and multiple colour configuration. - as Roxo Lighting KANTO /D

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.