



LED



Norms: EN 60598-1, EN 60598-2-4



IP 20

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Free-Standing.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Optical System: Diffuser: Microprismatic.

Control Gear: LED driver, TouchDIM, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

DAM - Microprismatic diffuser | Standard luminaire base


LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	kg	TouchDIM
LED	≤19	47	4850	70	68	300x885x2080	15,5	90367.L133.H

DAM - Microprismatic diffuser | "Type U" luminaire base

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	kg	TouchDIM
LED	≤19	47	4850	70	68	300x885x2080	14,5	90273.L133.H

COLOUR / FINISH

Code	Description
W/B	(1) White / (2) Black
W/G	(1) White / (2) Grey
G/W	(1) Grey / (2) White
G/B	(1) Grey / (2) Black
B/W	(1) Black / (2) White
B/G	(1) Black / (2) Grey



Subtitle:
(1) Luminaire and luminaire base colour finish
(2) Pole colour finish

• The finish order code is based on two colours, where (1) is the luminaire and luminaire base colour finish and (2) is the pole colour finish.

DETAILS



Touch panel with TouchDIM technology

Example code for order: 90367.L133.H (TouchDIM) + W/B (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature


Order code
3000

3000K




PHOTOMETRY

DIMENSIONS



KANTO 33W
DAM 4000K



TO SPECIFY:

Modern design LED free standing luminaire. Extruded aluminium body, powder coated in epoxy-polyester and high glare control microprismatic diffuser (UGR<19). Standard total luminous flux of 4850 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Standard version with TouchDIM light control panel, ergonomically integrated into the luminaire stand. Flat steel base for good stability and space saving positioning within office furniture. Optional 3000K and multiple colour configuration. - as Roxo Lighting KANTO

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.