



LED



Norms: EN 60598-1



IP 20

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Indirect.


Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.




Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.


DOZ - Opal polycarbonate diffuser

	LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	LED	8	854	71	70	60x630x150	1,0	90274.L106.E	90274.L106.H

COLOUR / FINISH


Code	Description
 W	White
 G	Grey
 B	Black
• Other colours under request.	

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000

Example code for order: 90274.L106.H (DALI) + W (COLOUR/FINISH) +3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

DETAILS




Front view



Side view

PHOTOMETRY



KANTO /W 8W
DOZ 4000K

TO SPECIFY:

Modern design LED wall mounted luminaire. Extruded aluminium body, powder coated in epoxy-polyester and opal polycarbonate diffuser. Standard total luminous flux of 854 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K. - as Roxo Lighting KANTO /W

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.