



LED

Norms: EN 60598-1, EN 60598-2-25



PRODUCT DESCRIPTION

Areas of Application: Hospitals, Restaurant and Hotel services, Cleanrooms.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 65.000h life (@L90, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.
Frame: Extruded aluminium.

Surface Finish: Powder coated in white matt.

Fixing system: Brackets.

DAM - Microprismatic diffuser.




LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)		K1	K3	Kg	HF	DALI
	≤19	30	4080	95	70	897x297x118	880x280	•	•	4,0	9Z7N.130.6V.F4	9Z7N.130.6V.E4
	≤19	39	5440	96	69	1197x297x118	1480x280	•	•	5,3	9Z7N.140.6V.F4	9Z7N.140.6V.E4
	≤19	47	6800	98	68	1497x297x118	1480x280	•	•	6,5	9Z7N.150.6V.F4	9Z7N.150.6V.E4
	≤19	39	5440	105	75	597x597x118	580x580	•	•	4,5	9Z7N.410.6V.F4	9Z7N.410.6V.E4

DOZ - Opal polycarbonate diffuser.



LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)		K1	K3	Kg	HF	DALI
	≤22	30	4080	91	67	897x297x118	880x280	•	•	4,0	9Z7N.130.2J.F4	9Z7N.130.2J.E4
	≤22	39	5440	92	66	1197x297x118	1180x280	•	•	5,3	9Z7N.140.2J.F4	9Z7N.140.2J.E4
	≤22	47	6800	95	66	1497x297x118	1480x280	•	•	6,5	9Z7N.150.2J.F4	9Z7N.150.2J.E4
	≤22	39	5440	99	71	597x597x118	580x580	•	•	4,5	9Z7N.410.2J.F4	9Z7N.410.2J.E4

DETAILS




Pull-up version detail

Example code for order: 9Z7N.140.6V.E4 (DALI) + 3000 + 965403 + 965401 + 955000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Connectors



Connector 3-pole Wieland GST18i3 male
Connector 5-pole Wieland GST18i5 male
Connector 5-pole Wieland GST18i5 DIM male

Order code
965301
965401
965403

Safety cable



Steel safety cable

Order code
955000

Emergency unit




Emergency unit 3 hours
Emergency unit 1 hour


Order code
K3
K1

• Includes test function by Telecommand signal.

PHOTOMETRY




LNE IP LED 39W DAM
(597x597mm) 4000K



LNE IP LED 39W DOZ
(597x597mm) 4000K


PERFORMANCE




LNE IP LED DAM

LED: 39W
DIMENSIONS: 8,5m x 5,5m
HEIGHT: 2,8m
MAINTENANCE: 0,8
REFLECTANCE: 70/50/20
WORKING PLACE: 0,8m
ILLUMINANCE E_m : 490 lux
UGR: ≤16


DIMENSIONS




FIXING SYSTEMS



Lay-in version for exposed T grids 15/24mm.



Pull-up version with brackets for exposed T grids 15/24mm.



Pull-up version with brackets for plasterboard ceilings.

TO SPECIFY:

LED recessed modular IP20/54 luminaire for pull-up version with brackets. Extruded aluminium frame available with microprismatic (DAM) or opal (DOZ) diffuser. Standard version with 4000K, CRI> 80 and 65000h lifetime (@L90, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, connectors and 1 or 3 hours emergency unit. – as Indelague LNE IP LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.