

PHOTOMETRIC RESULTS

Name:	LNS LED 39W DAM [597x597mm]		
Number:	01	Diameter:	0 mm
Report:	20-03-2017	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	80 mm
Number:	1	Power:	39,18 W
Lamp flux:	5440,00 lm	Operator:	INDEL AGUE GROUP
Date:	20-03-2017 11:39:06	Output ratio:	77,4 %

Protocol

LiTG-class: A40
UTE-class: 0,70 E
IES-class: 47 - 79 - 96 - 100 - 70
TM5-class: BZ4

Divergences in the plane through maximum intensity:

	Horizontal	Vertical
One half peak divergence	113,8°	112,9°
Half peak side angle (left)	-56,9°	-56,4°
Half peak side angle (right)	56,9°	56,4°
One tenth peak divergence	160,9°	160,7°
Tenth peak side angle (left)	-80,5°	-80,4°
Tenth peak side angle (right)	80,5°	80,4°


C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						

Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

PHOTOMETRIC RESULTS

Name:	LNS LED 39W DAM [597x597mm]		
Number:	01	Diameter:	0 mm
Report:	20-03-2017	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	80 mm
Number:	1	Power:	39,18 W
Lamp flux:	5440,00 lm	Operator:	INDELAGUE GROUP
Date:	20-03-2017 11:39:06	Output ratio:	77,4 %

Polar diagram LNS LED 39W DAM [597x597mm] / Direct in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	LNS LED 39W DAM [597x597mm]		
Number:	01	Diameter:	0 mm
Report:	20-03-2017	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	80 mm
Number:	1	Power:	39,18 W
Lamp flux:	5440,00 lm	Operator:	INDEL AGUE GROUP
Date:	20-03-2017 11:39:06	Output ratio:	77,4 %

UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	16,0	17,7	16,4	18,0	18,3	16,7	18,3	17,0	18,6	18,9
2H	3H	17,3	18,8	17,7	19,2	19,5	18,2	19,7	18,6	20,0	20,3
2H	4H	17,8	19,2	18,2	19,5	19,9	18,7	20,2	19,1	20,5	20,9
2H	6H	18,1	19,4	18,5	19,7	20,1	19,1	20,4	19,5	20,8	21,2
2H	8H	18,1	19,3	18,5	19,7	20,1	19,2	20,5	19,6	20,8	21,2
2H	12H	18,1	19,3	18,5	19,7	20,1	19,2	20,4	19,6	20,8	21,2
4H	2H	16,7	18,1	17,1	18,5	18,8	17,2	18,6	17,6	19,0	19,4
4H	3H	18,2	19,4	18,6	19,8	20,2	18,9	20,1	19,3	20,5	20,9
4H	4H	18,8	19,8	19,2	20,2	20,7	19,6	20,7	20,0	21,1	21,5
4H	6H	19,1	20,0	19,5	20,5	20,9	20,0	21,0	20,5	21,4	21,8
4H	8H	19,2	20,0	19,6	20,5	20,9	20,1	21,0	20,6	21,5	21,9
4H	12H	19,2	20,0	19,7	20,5	21,0	20,2	21,0	20,7	21,5	22,0
8H	4H	19,0	19,9	19,5	20,3	20,8	19,7	20,6	20,2	21,1	21,5
8H	6H	19,4	20,1	19,9	20,6	21,1	20,2	21,0	20,7	21,4	21,9
8H	8H	19,5	20,2	20,1	20,7	21,2	20,5	21,1	21,0	21,6	22,1
8H	12H	19,6	20,1	20,1	20,7	21,2	20,6	21,1	21,1	21,6	22,1
12H	4H	19,0	19,8	19,5	20,3	20,8	19,8	20,6	20,2	21,0	21,5
12H	6H	19,5	20,1	20,0	20,6	21,1	20,3	21,0	20,8	21,5	21,9
12H	8H	19,6	20,1	20,1	20,6	21,2	20,5	21,0	21,0	21,5	22,1

UGR values are corrected for lamp flux of 6800 lm by 6,7

PHOTOMETRIC RESULTS

Name:	LNS LED 39W DAM [597x597mm]		
Number:	01	Diameter:	0 mm
Report:	20-03-2017	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	80 mm
Number:	1	Power:	39,18 W
Lamp flux:	5440,00 lm	Operator:	INDEL AGUE GROUP
Date:	20-03-2017 11:39:06	Output ratio:	77,4 %

Luminance [cd/m²] LNS LED 39W DAM [597x597mm] / Direct in 15° C / 5° G

G/C [cd/	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	3779,77	3734,04	3755,53	3786,23	3776,89	3759,53	3795,16	3759,53	3776,89
50,00	3210,38	3176,69	3200,53	2999,33	3200,64	3233,51	3263,33	3233,51	3200,64
55,00	2573,22	2703,06	2367,07	2006,55	2311,34	2725,61	2676,74	2725,61	2311,34
60,00	2129,98	2150,54	1612,45	1621,00	1680,35	2170,75	2168,28	2170,75	1680,35
65,00	1733,45	1681,37	1220,15	1389,47	1299,16	1680,65	1671,43	1680,65	1299,16
70,00	1304,44	1384,75	1144,13	1112,17	1166,21	1309,91	1333,85	1309,91	1166,21
75,00	1039,73	1089,30	962,78	899,30	932,38	1066,33	1082,07	1066,33	932,38
80,00	881,23	861,76	817,10	843,86	795,70	865,42	920,34	865,42	795,70
85,00	586,97	610,97	621,14	559,86	612,02	611,37	578,80	611,37	612,02

G/C [cd/	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	3786,23	3755,53	3734,04	3779,77	3734,04	3755,53	3786,23	3776,89	3759,53
50,00	2999,33	3200,53	3176,69	3210,38	3176,69	3200,53	2999,33	3200,64	3233,51
55,00	2006,55	2367,07	2703,06	2573,22	2703,06	2367,07	2006,55	2311,34	2725,61
60,00	1621,00	1612,45	2150,54	2129,98	2150,54	1612,45	1621,00	1680,35	2170,75
65,00	1389,47	1220,15	1681,37	1733,45	1681,37	1220,15	1389,47	1299,16	1680,65
70,00	1112,17	1144,13	1384,75	1304,44	1384,75	1144,13	1112,17	1166,21	1309,91
75,00	899,30	962,78	1089,30	1039,73	1089,30	962,78	899,30	932,38	1066,33
80,00	843,86	817,10	861,76	881,23	861,76	817,10	843,86	795,70	865,42
85,00	559,86	621,14	610,97	586,97	610,97	621,14	559,86	612,02	611,37

G/C [cd/	270,00	285,00	300,00	315,00	330,00	345,00
45,00	3795,16	3759,53	3776,89	3786,23	3755,53	3734,04
50,00	3263,33	3233,51	3200,64	2999,33	3200,53	3176,69
55,00	2676,74	2725,61	2311,34	2006,55	2367,07	2703,06
60,00	2168,28	2170,75	1680,35	1621,00	1612,45	2150,54
65,00	1671,43	1680,65	1299,16	1389,47	1220,15	1681,37
70,00	1333,85	1309,91	1166,21	1112,17	1144,13	1384,75
75,00	1082,07	1066,33	932,38	899,30	962,78	1089,30
80,00	920,34	865,42	795,70	843,86	817,10	861,76
85,00	578,80	611,37	612,02	559,86	621,14	610,97

HEADQUARTERS

INDÚSTRIA ELÉTRICA DE ÁGUEDA S.A.

Rua da Mina 465 | Covão | Zona industrial EN1 Norte

3750-792 Trofa ÁGUEDA | PORTUGAL

www.indelague.com | www.roxolighting.com

indelague@indelague.pt | roxo.london@roxolighting.com

Tel. (+351) 234 612 310

Fax (+351) 234 624 058