

Norms: EN 60598-1, EN 60598-2-25



PRODUCT DESCRIPTION

Areas of Application: Hospitals, Restaurant and Hotel services, Cleanrooms.

Mounting: Surface.


Light Distribution: Direct.

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.
Frame: Extruded aluminium.

Surface Finish: Powder coated in white matt (RAL9016).

DAM - Microprismatic diffuser



LAMP*	UGR	W	Lm/W	η(%)	AxBxC (mm)	Kg	HF	DSI	DALI
T5	≤19	3x14	62	81	597x597x68	5	9R4D.314.6V.A4	9R4D.314.6V.84	9R4D.314.6V.74
	≤22	3x24	60	86	597x597x68	5	9R4D.324.6V.A4	9R4D.324.6V.84	9R4D.324.6V.74
	≤19	4x14	63	81	597x597x68	5	9R4D.414.6V.A4	9R4D.414.6V.84	9R4D.414.6V.74
	≤22	4x24	63	88	597x597x68	5	9R4D.424.6V.A4	9R4D.424.6V.84	9R4D.424.6V.74

DOP - Opal polycarbonate diffuser



LAMP*	UGR	W	Lm/W	η(%)	AxBxC (mm)	Kg	HF	DSI	DALI
T5	≤19	3x14	48	62	597x597x68	5	9R4D.314.21.A4	9R4D.314.21.84	9R4D.314.21.74
	≤22	3x24	46	66	597x597x68	5	9R4D.324.21.A4	9R4D.324.21.84	9R4D.324.21.74
	≤22	4x14	48	63	597x597x68	5	9R4D.414.21.A4	9R4D.414.21.84	9R4D.414.21.74
	≤22	4x24	50	70	597x597x68	5	9R4D.424.21.A4	9R4D.424.21.84	9R4D.424.21.74

OPTIONS

Code	Description
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
--	Lamps as optional.

DETAILS



Security cable


* Lamp not included.
Example code for order: 9R4D.424.6V.74 (DALI)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.



PHOTOMETRY

DIMENSIONS

LNS IP 3x24W DAM
Lamp: 3 x 24W/840 HO



LNS IP 4x24W DOP
Lamp: 4 x 24W/840 HO



TO SPECIFY:

IP54 surface mounted T5(G5) clean room luminaire. Aluminium frame available with microprismatic or opal diffuser. Equipped with HF control gear. Dimmable version and emergency also available – as Indelague LNS IP.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.