



LED



Norms: EN 60598-1, EN 60598-2-1



IP 40

DAM
650°C

DOZ
850°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

Mounting: Ceiling surface.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated in white matt.

DAM - Microprismatic diffuser



LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI
LED	≤19	30	4080	99	73	872x297x80	•	•	7,1	9Y92.130.6V.F4	9Y92.130.6V.E4
	≤19	39	5440	103	74	1149x297x80	•	•	8,3	9Y92.140.6V.F4	9Y92.140.6V.E4
	≤19	47	6800	106	73	1424x297x80	•	•	10,0	9Y92.150.6V.F4	9Y92.150.6V.E4
	≤19	39	5440	107	77	597x597x80	•	•	8,3	9Y92.410.6V.F4	9Y92.410.6V.E4

DOZ - Opal polycarbonate diffuser



LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI
LED	≤22	30	4080	97	71	872x297x80	•	•	7,1	9Y92.130.2J.F4	9Y92.130.2J.E4
	≤22	39	5440	98	70	1149x297x80	•	•	8,3	9Y92.140.2J.F4	9Y92.140.2J.E4
	≤22	47	6800	101	70	1424x297x80	•	•	10,0	9Y92.150.2J.F4	9Y92.150.2J.E4
	≤22	39	5440	103	74	597x597x80	•	•	8,3	9Y92.410.2J.F4	9Y92.410.2J.E4

DETAILS




Frame with click system

Example code for order: 9Y92.150.2J.E4 (DALI) + 3000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

CRI



CRI>90

Order code
CRI90

Emergency unit




Emergency unit 3 hours
Emergency unit 1 hour


Order code
K3
K1

- Test function by telecommand signal.

PHOTOMETRY




LNS LED 39W DAM
(597x597mm) 3000K



LNS LED 39W DOZ
(597x597mm) 4000K

DIMENSIONS



872/1149/1424

TO SPECIFY:

Surface LED luminaire. Frame without visible screws and opal polycarbonate or microprismatic diffuser. Standard version with 4000K, CRI>80, total luminous flux of 4080 / 6800 lm and 50.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, CRI>90 and 1 or 3 hours emergency unit. – as Indelague LNS LED

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.