



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

Mounting: Surface/Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 65.000h life time (@L80, B10, Ta 25 C)

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.
Diffuser: Polycarbonate.

Surface Finish: Powder coated in white matt.

bLINE - Opal polycarbonate diffuser

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
LED	22	2415	76	69	877x106x78	2,9	9Y5D.116.8J.F4	9Y5D.116.8J.E4
	26	3220	84	68	1157x106x78	2,9	9Y5D.122.8J.F4	9Y5D.122.8J.E4
	31	4025	88	68	1442x106x78	3,5	9Y5D.127.8J.F4	9Y5D.127.8J.E4


DETAILS



Clip-in polycarbonate diffuser

OPTIONS


Colour temperature



3000K
Tunable White

Order code
3000
T000

Ceiling rose



Square ceiling rose
Surface mounted
Recessed

Order code
971700
971400

Example code for order: 9Y5D.122.8J.E4 (DALI) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

Current supply cable

Order code




1,5m transparent cable 0,75mm2
3x0,75mm2
5x0,75mm2

940400
940500

Suspension

Order code




Suspension type "I" (x2)


910001

PHOTOMETRY


DIMENSIONS



LNS Mini LED 22W
bLINE 4000K



LNS Mini LED 26W
bLINE 4000K



TO SPECIFY:

Surface LED luminaire, individually mounted with bLINE polycarbonate diffuser and total luminous flux of 2415 / 4025 lm. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, transparent current supply cable and ceiling rose. – as Roxo Lighting LNS Mini LED.