



LED



Norms: EN 60598-1, EN 60598-2-1



IP 20

960°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

Mounting: Surface/Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 65.000h life time (@L80, B10, Ta 25 C)

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.
Diffuser: Polycarbonate.

Surface Finish: Powder coated in white matt.

bLINE - Difusor de policarbonato opal



LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
LED	15	1610	72	67	565x106x78	1,5	9Y5E.111.8J.F4	9Y5E.111.8J.E4
	22	2415	76	69	850x106x78	2,9	9Y5E.116.8J.F4	9Y5E.116.8J.E4
	26	3220	84	68	1130x106x78	2,9	9Y5E.122.8J.F4	9Y5E.122.8J.E4
	31	4025	88	68	1442x106x78	3,5	9Y5E.127.8J.F4	9Y5E.127.8J.E4

Please note:

- To complete a line, start kit will be necessary. Please order separately.
- Dimensions without end caps, please add 28mm to complete the line.
- 565mm version only available as end part of the line.

DETAILS



Clip-in diffuser system

Example code for order: (3x) 9Y5E.127.8J.E4 (DALI) + 3000 + 921300 + (2x) 9453 + (2x) 965100 + 971700 + 940000 + (3x) 910001(OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K
Tunable White

Order code
3000
T000

Start kit




Start Kit - Start / End

• Two end caps and one cable lock, includes screws.

Order code
921300

Through-wiring



1,5 mm² through-wiring
3 x 1,5 mm²
5 x 1,5 mm²
2,5 mm² through-wiring
3 x 2,5 mm²
5 x 2,5 mm²

Order code
9452
9453
9454
9455

Connectors



KIT 3-pole Mini Wieland GST15i3 (male and female) **965000**
Connector 3-pole Mini Wieland GST15i3 male **965001**
Connector 3-pole Mini Wieland GST15i3 female **965002**
KIT 5-pole Mini Wieland GST15i5 DIM (male and female) **965100**
Connector 5-pole Mini Wieland GST15i5 DIM male **965101**
Connector 5-pole Mini Wieland GST15i5 DIM female **965102**

Order code

Ceiling rose



Square ceiling rose
Surface mounted
Recessed

Order code
971700
971400


Current supply cable



1,5m transparent cable 0,75mm²
3x0,75mm²
5x0,75mm²
1,5m transparent cable 1,5mm²
3x1,5mm²
5x1,5mm²

Order code
940400
940500
940300
940000


Suspension




Suspension type "I" (x2)

Order code
910001

PHOTOMETRY




LNS Mini LED Line 22W
bLINE 4000K



LNS Mini LED Line 26W
bLINE 4000K

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

DIMENSIONS



TO SPECIFY:

Surface LED luminaire for continuous line with bLINE polycarbonate diffuser and total luminous flux of 1610 / 4025 lm. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, transparent current supply cable and ceiling rose. – as Indelague LNS Mini LED Line.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.