



LED



Norms: EN 60598-1, EN 60598-2-1



IP 20

960°C

230V/50Hz

### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Offices, Schools, Corridors.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 65.000h life time (@L80, B10, Ta 25 C)

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.  
Diffuser: Polycarbonate.

**Surface Finish:** Powder coated in white matt.

### bLINE - Difusor de policarbonato opal

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
LED	15	1610	72	67	565x106x78	1,5	9Y5E.111.8J.F4	9Y5E.111.8J.E4
	22	2415	76	69	850x106x78	2,9	9Y5E.116.8J.F4	9Y5E.116.8J.E4
	26	3220	84	68	1130x106x78	2,9	9Y5E.122.8J.F4	9Y5E.122.8J.E4
	31	4025	88	68	1442x106x78	3,5	9Y5E.127.8J.F4	9Y5E.127.8J.E4

- Please note:
- To complete a line, start kit will be necessary. Please order separately.
  - Dimensions without end caps, please add 28mm to complete the line.
  - 565mm version only available as end part of the line.

### DETAILS



Clip-in diffuser system

Example code for order: (3x) 9Y5E.127.8J.E4 (DALI) + 3000 + 921300 + (2x) 9453 + (2x) 965100 + 971700 + 940000 + (3x) 910001(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature



3000K  
Tunable White

Order code  
**3000**  
**T000**

#### Start kit




Start Kit - Start / End

• Two end caps and one cable lock, includes screws.

Order code  
**921300**

#### Through-wiring



1,5 mm<sup>2</sup> through-wiring  
3 x 1,5 mm<sup>2</sup>  
5 x 1,5 mm<sup>2</sup>  
2,5 mm<sup>2</sup> through-wiring  
3 x 2,5 mm<sup>2</sup>  
5 x 2,5 mm<sup>2</sup>

Order code  
**9452**  
**9453**  
**9454**  
**9455**

#### Connectors



KIT 3-pole Mini Wieland GST15i3 (male and female) **965000**  
Connector 3-pole Mini Wieland GST15i3 male **965001**  
Connector 3-pole Mini Wieland GST15i3 female **965002**  
KIT 5-pole Mini Wieland GST15i5 DIM (male and female) **965100**  
Connector 5-pole Mini Wieland GST15i5 DIM male **965101**  
Connector 5-pole Mini Wieland GST15i5 DIM female **965102**

Order code  
**965000**  
**965001**  
**965002**  
**965100**  
**965101**  
**965102**

#### Ceiling rose



Square ceiling rose  
Surface mounted  
Recessed

Order code  
**971700**  
**971400**

#### Current supply cable



1,5m transparent cable 0,75mm<sup>2</sup>  
3x0,75mm<sup>2</sup>  
5x0,75mm<sup>2</sup>  
1,5m transparent cable 1,5mm<sup>2</sup>  
3x1,5mm<sup>2</sup>  
5x1,5mm<sup>2</sup>

Order code  
**940400**  
**940500**  
**940300**  
**940000**


#### Suspension




Suspension type "I" (x2)

Order code  
**910001**

### PHOTOMETRY




LNS Mini LED Line 22W  
bLINE 4000K



LNS Mini LED Line 26W  
bLINE 4000K

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## DIMENSIONS



### TO SPECIFY:

Surface LED luminaire for continuous line with bLINE polycarbonate diffuser and total luminous flux of 1610 / 4025 lm. Standard version with 4000K, CRI>80 and 65.000h lifetime (@ L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, suspension, transparent current supply cable and ceiling rose. – as Roxo Lighting LNS Mini LED Line.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.