

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Industrial areas, commercial areas.

Mounting: Suspended.

Light Distribution: Direct.

Control Gear: Magnetic ballast, ignitor and capacitor.

Materials: Body: Galvanized steel.

Surface Finish: Powder coated in grey.



RLO - Satin aluminium reflector

	LAMP*		W	AxB (mm)	Kg	ORDER CODE
	HIE	E40	250	Ø485x545	6	9D0D.250.0N4
		E40	400	Ø485x545	6,8	9D0D.400.0N4
	HSE-E	E40	250	Ø485x545	6	9F0D.250.0N4
		E40	400	Ø485x545	6,8	9F0D.400.0N4

OPTIONS

Code	Description
925100	Wire grid protection.
612	Transparent glass.
--	Lamps as optional.

DETAILS




Wire grid protection as optional

* Lamp not included.
Example code for order: 9F0D.250.0N4 (ORDER CODE) + 925100 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

DIMENSIONS



TO SPECIFY:

Suspended high bay luminaire suitable for 1x250/400W high pressure sodium or metal halide lamp. Aluminium reflector with high efficiency. Optional transparent tempered glass, wire grip protection – as Indelague MBF.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.