

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Industrial areas, commercial areas.

**Mounting:** Suspended.

**Light Distribution:** Direct.

**Control Gear:** Magnetic ballast, ignitor and capacitor.

**Materials:** Body: Galvanized steel.

**Surface Finish:** Powder coated in grey.



RLO - Satin aluminium reflector

	LAMP*		W	AxB (mm)	Kg	ORDER CODE
	HIE	E40	250	Ø485x545	6	9D0D.250.0N4
		E40	400	Ø485x545	6,8	9D0D.400.0N4
	HSE-E	E40	250	Ø485x545	6	9F0D.250.0N4
		E40	400	Ø485x545	6,8	9F0D.400.0N4

**OPTIONS**

Code	Description
925100	Wire grid protection.
612	Transparent glass.
--	Lamps as optional.

**DETAILS**




Wire grid protection as optional

\* Lamp not included.  
Example code for order: 9F0D.250.0N4 (ORDER CODE) + 925100 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

**DIMENSIONS**



**TO SPECIFY:**

Suspended high bay luminaire suitable for 1x250/400W high pressure sodium or metal halide lamp. Aluminium reflector with high efficiency. Optional transparent tempered glass, wire grip protection – as Roxo Lighting MBF.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.