

LED



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.


Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.


Surface Finish: Powder coated.

Fixing system: Brackets.













gCONTROL+ - Microprismatic polycarbonate diffuser PLUS

	LAMP	W	lm	lm/W	η(%)	AxB (mm)	Φ	K1	K3	kg	HF	DALI
	LED	24	2600	77	71	Ø400x105	Ø385	•	•	5,4	90038.L122.E	90038.L122.H
		36	4092	72	63	Ø400x105	Ø385	•	•	5,4	90038.L135.E	90038.L135.H

DOZ - Opal polycarbonate diffuser

	LAMP	W	lm	lm/W	η(%)	AxB (mm)	Φ	K1	K3	kg	HF	DALI
	LED	24	2600	86	79	Ø400x105	Ø385	•	•	5,4	90135.L122.E	90135.L122.H
		36	4092	81	71	Ø400x105	Ø385	•	•	5,4	90135.L134.E	90135.L134.H

COLOUR / FINISH

Code	Description
 W	White
 G	Grey
 B	Black
 U	Blue
 V	Green
 T	Yellow
 K	Red (RAL 3020)
 N	Jungle
 D	Golden eye
 O	Sahara
 L	Autumn
 R	Rusty chain


Example code for order: 90038.L135.H (DALI) + W (COLOUR/FINISH) + W5MD + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
C	Pure chocolate
1	Mist
9	Dark rock
I	Carbon

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000

Connectors



Connector 3-pole wieland GST 18i3 male
Connector 5-pole wieland GST 18i5 male
Connector 5-pole wieland GST 18i5 DIM male

Order code
W3M
W5M
W5MD

Safety cable



Steel safety cable

Order code
955000

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

Order code
K3
K1

• Test function by telecommand signal.

DETAILS




LED detail




Bracket detail

PHOTOMETRY



MUSER Ring LED 24W
gCONTROL+ 4000K



MUSER Ring LED 24W
DOZ 4000K

TO SPECIFY:

Recessed circular LED luminaire. Equipped with 2600/4092 lumen light engine and circular polycarbonate microprismatic gCONTROL+, or DOZ opal polycarbonate diffuser. Standard version with LED 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable driver, 3000K, 1 or 3 hours emergency unit or connectors version. Available in 16 different colours – as Roxo Lighting MUSER Ring LED.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.