



LED

Norms: EN 60598-1, EN 60598-2-4



PRODUCT DESCRIPTION

Areas of Application: Housing, Offices, Hotel, Art and Culture Spaces.

Mounting: Desk.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>90, 60.000h life (@L80, B10, Ta 25 C).

Optical System: Diffuser: Opal acrylic.

Control Gear: 24V Transformer.

Materials: Base and tube:metal; Top part: wood.

Surface Finish: Powder coated; Top part rosewood or powder coated.

DAZ - Opal acrylic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	TouchDIM
	≤19	5	520	61	59%	Ø250x26x356	1,5	90306.L009.H

COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
J	Rosewood

Note: Tube and base always in black.


DETAILS



TouchDIM

OPTIONS

Colour temperature



2700K


Order code
2700

Example code for order: 90306.L009.E (TouchDIM) + W(COLOUR/FINISH) + 2700(OPTIONS)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

DIMENSIONS



NOAH /D 5W
DAZ 4000K



TO SPECIFY:

Circular LED desk luminaire. Metal base and tube, epoxy-polyester powder coated, and top part in rosewood, white, grey or black finish. With opal acrylic diffuser DAZ. Standard version with LED strip 4000K, CRI>90 and 60.000h lifetime (@L80, B10, Ta 25 C). With TouchDim push-button. Optional 2700K version - as Indelague NOAH /D

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.