



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, MacAdam Step<3, 60.000h life (@L90, B10, Ta 25 C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.

Fixing system: Brackets.


bLINE - Opal polycarbonate diffuser

LED	UGR	W	lm	lm/W	η(%)	AxBxC (mm)		kg	HF	DALI
	≤25	25	3741	87	58	863x50x80	850x41	2,3	90449.L003.E	90449.L003.H
	≤25	32	4988	92	59	1143x50x80	1130x41	2,8	90449.L004.E	90449.L004.H
	≤25	40	6235	90	58	1423x50x80	1410x41	3,3	90449.L005.E	90449.L005.H
	≤25	47	7482	91	57	1703x50x80	1690x41	3,8	90449.L006.E	90449.L006.H
	-	57	8729	90	59	1985x50x80	1972x41	4,6	90449.L007.E	90449.L007.H
	-	64	9976	92	59	2265x50x80	2252x41	5,1	90449.L008.E	90449.L008.H
	-	72	11223	92	59	2545x50x80	2532x41	5,6	90449.L009.E	90449.L009.H
	-	80	12470	90	58	2825x50x80	2812x41	6,1	90449.L010.E	90449.L010.H

COLOUR / FINISH

Code	Description
W	White
B	Black

DIMENSIONS



Example code for order: 90449.L003.E (HF) + 3000 + 955000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K
Tunable White

Order code
3000
T000

SwitchDIM Tunable White



SwitchDIM Tunable White.

Order code
926600

Steel safety cable



Steel safety cable

Order code
955000

Low power option




Option supplied under request.


DETAILS



Clip-in diffuser system




Bracket



End caps without visible screws

PHOTOMETRY



REBA 35 /E LED
L1143 bLINE 4000K

TO SPECIFY:

Linear recessed LED luminaire, with trim, individually mounted. Extruded aluminium profile, anodised in natural colour and 50mm width. Injected polycarbonate end caps, without visible screws, and clip-in polycarbonate bLINE diffuser. Standard version with LED 4000K, CRI>80, MacAdam Step<3 and 60.000h lifetime (@L90, B10, Ta 25 C). Optional DALI dimmable LED driver, 3000K and Tunable White. - as Roxo Lighting REBA 35 /E LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.