



LED



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.


bLINE - Opal polycarbonate diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	K1	K3	kg	HF	DALI
LED	≤25	30	3870	84	65	848x65x80	-	-	2,5	90339.L130.E	90339.L130.H
	≤25	39	5160	90	68	1128x65x80	-	-	3,0	90339.L140.E	90339.L140.H
	≤25	47	6450	88	64	1408x65x80	•	•	3,5	90339.L150.E	90339.L150.H

COLOUR / FINISH

Code	Description
W	White
B	Black

DIMENSIONS



OPTIONS

Colour temperature



3000K
Tunable white

Order code
3000
T000

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

• Test function by telecommand signal.

Order code
K3
K1

Example code for order: 90339.L150.E (HF) + 3000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

Low power version



Option supplied under request.

Bespoke projects



Option supplied under request.

DETAILS




Clip-in diffuser system



End caps without visible screws

PHOTOMETRY



REBA 65 /P LED 39W
bLINE 4000K

TO SPECIFY:

Linear wall mounted LED luminaire, individually mounted and 65 mm width. Extruded aluminium profile, anodised in natural colour. Polycarbonate end caps without visible screws and polycarbonate bLINE diffuser. Standard version with 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional 3000K, DALI dimmable driver, TunableWhite technology and 1 or 3 hours emergency unit. – as Roxo Lighting REBA 65 /P LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.