



LED



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.

Fixing system: Trimless brackets.

bGLARE - Microprismatic diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	█	K1	K3	kg	HF	DALI
LED	≤19	24	3039	80	63	848x65x80	849x66	-	-	2,5	90335.L130.E	90335.L130.H
	≤19	30	4052	88	65	1128x65x80	1129x66	-	-	3	90335.L140.E	90335.L140.H
	≤19	37	5065	88	64	1408x65x80	1409x66	•	•	3,5	90335.L150.E	90335.L150.H
	≤19	42	6078	91	63	1688x65x80	1689x66	•	•	5	90335.L160.E	90335.L160.H
	-	49	7091	93	64	1970x65x80	1971x66	•	•	5,5	90335.L170.E	90335.L170.H
	-	61	8104	85	64	2250x65x80	2251x66	•	•	6	90335.L180.E	90335.L180.H
	-	67	9117	88	65	2530x65x80	2531x66	•	•	6,5	90335.L190.E	90335.L190.H
	-	74	10130	88	64	2810x65x80	2811x66	•	•	7	90335.L100.E	90335.L100.H


bLINE - Opal polycarbonate diffuser

LAMP	UGR	W	lm	lm/W	η(%)	AxBxC (mm)	█	K1	K3	Kg	HF	DALI
LED	≤25	30	3870	84	65	848x65x80	849x66	-	-	2,5	90334.L130.E	90334.L130.H
	≤25	39	5160	90	68	1128x65x80	1129x66	-	-	3	90334.L140.E	90334.L140.H
	≤25	47	6450	88	64	1408x65x80	1409x66	•	•	3,5	90334.L150.E	90334.L150.H
	≤25	56	7740	90	65	1688x65x80	1689x66	•	•	5	90334.L160.E	90334.L160.H
	-	64	9030	95	67	1970x65x80	1971x66	•	•	5,5	90334.L170.E	90334.L170.H
	-	77	10320	87	65	2250x65x80	2251x66	•	•	6	90334.L180.E	90334.L180.H
	-	86	11610	89	66	2530x65x80	2531x66	•	•	6,5	90334.L190.E	90334.L190.H
	-	94	12900	88	64	2810x65x80	2811x66	•	•	7	90334.L100.E	90334.L100.H

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



Example code for order: 90335.L150.E (HF) + 3000 + K3 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K
Tunable White

Order code
3000
T000

Steel safety cable



Steel safety cable

Order code
955000

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

- Test function by telecommand signal.

Order code
K3
K1

Low power option



Option supplied under request


DETAILS



Clip-in diffuser system




Trimless bracket




End caps without visible screws

PHOTOMETRY



REBA 65 /T LED 30W
bGLARE 4000K



REBA 65 /T LED 39W
bLINE 4000K

TO SPECIFY:

Linear recessed trimless LED luminaire, individually mounted and 65 mm width. Extruded aluminium profile, anodized in natural colour. Polycarbonate screwless end caps and polycarbonate bLINE or bGLARE diffuser. Standard version with 4000K, CRI>80 and 50000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable driver and 3000K or TunableWhite technology and 1 or 3 hours emergency unit. – as Roxo Lighting REBA 65 /T LED

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.