

Norms: EN 60598-1, EN 60598-2-2



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** T5 (G5) lamp.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium profile.

**Surface Finish:** Anodised in natural colour.

**Fixing system:** Brackets.



PB - Polished double parabolic louvre | T0 (Trimless version)

LAMP*	UGR	W	η(%)	AxBxC (mm)		Kg	HF	DSI	DALI
	≤19	1x14	64	591x50x70	592x51	1,2	90201.P114.A	90201.P114.C	90201.P114.D
	≤22	1x21	64	891x50x70	892x51	1,6	90201.P121.A	90201.P121.C	90201.P121.D
	≤22	1x24	69	591x50x70	592x51	1,2	90201.P124.A	90201.P124.C	90201.P124.D
	≤22	1x28	68	1191x50x70	1192x51	2	90201.P128.A	90201.P128.C	90201.P128.D
	≤22	1x35	65	1491x50x70	1492x51	2,5	90201.P135.A	90201.P135.C	90201.P135.D
	≤22	1x39	62	891x50x70	892x51	1,6	90201.P139.A	90201.P139.C	90201.P139.D
	≤22	1x49	70	1491x50x70	1492x51	2,5	90201.P149.A	90201.P149.C	90201.P149.D
	≤25	1x54	65	1191x50x70	1192x51	2	90201.P154.A	90201.P154.C	90201.P154.D
	≤25	1x80	72	1491x50x70	1492x51	2,5	90201.P180.A	90201.P180.C	90201.P180.D

BLINE - Opal polycarbonate diffuser | T0 (Trimless version)

LAMP*	UGR	W	η(%)	AxBxC (mm)		Kg	HF	DSI	DALI
	≤19	1x14	42	591x50x70	592x51	1,2	90195.P114.A	90195.P114.C	90195.P114.D
	≤19	1x21	40	891x50x70	892x51	1,6	90195.P121.A	90195.P121.C	90195.P121.D
	≤22	1x24	44	591x50x70	592x51	1,2	90195.P124.A	90195.P124.C	90195.P124.D
	≤22	1x28	55	1191x50x70	1192x51	2	90195.P128.A	90195.P128.C	90195.P128.D
	≤22	1x35	51	1491x50x70	1492x51	2,5	90195.P135.A	90195.P135.C	90195.P135.D
	≤22	1x39	36	891x50x70	892x51	1,6	90195.P139.A	90195.P139.C	90195.P139.D
	≤22	1x49	44	1491x50x70	1492x51	2,5	90195.P149.A	90195.P149.C	90195.P149.D
	≤22	1x54	44	1191x50x70	1192x51	2	90195.P154.A	90195.P154.C	90195.P154.D
	≤22	1x80	47	1491x50x70	1492x51	2,5	90195.P180.A	90195.P180.C	90195.P180.D

\*Lamp not included.

Example code for order: 90201.P149.D (DALI) + 9851 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.


### COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

### OPTIONS

#### Application type

Order code  
**9851**




T1 (Trim version)


- Additional "L" bracket.

Please note:  
This option can be supplied on request.

### DETAILS




Clip-in polycarbonate diffuser.




Clip-in aluminium louvre.

### PHOTOMETRY

**REBA /E 1x35W BLINE**  
Lamp: 1 x 35W/840 HE




**REBA /E 1x80W PB**  
Lamp: 1 x 80W/840 HO




### DIMENSIONS

T0 (Trimless)




T1 (Trim)



### RECESS DIMENSIONS

T0 (Trimless)

 For this version the cutting width is 51 mm.




T1 (Trim)

 For this version the cutting width is 65 mm.



We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

T1 (Trim)

W	A1xB1xC1 (mm)	
1x14	591x72x74	592x65
1x21	891x72x74	892x65
1x24	591x72x74	592x65
1x28	1191x72x74	1192x65
1x35	1491x72x74	1492x65
1x39	891x72x74	892x65
1x49	1491x72x74	1492x65
1x54	1191x72x74	1192x65
1x80	1491x72x74	1492x65

**TO SPECIFY:**

Trimless linear recessed T5(G5) luminaire, individually mounted with 50mm width extruded aluminium profile, anodised in natural colour. Aluminium end caps and PB louvre or BLINE polycarbonate diffuser. Available with HF, DSI or DALI control gear. Optional trim version – as Indelague REBA /E.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.