

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: T5 (G5) lamp.


Control Gear: Electronic equipment, 220-240VAC-50/60Hz.



Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.


Fixing system: Brackets.



PB - Polished double parabolic louvre (middle) | T0 (Trimless version)

LAMP	UGR	W	η.(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
	≤19	1x14**	64	585x50x70	585x51	1,2	90202.P114.A	90202.P114.C	90202.P114.D
	≤22	1x21	64	885x50x70	885x51	1,6	90202.P121.A	90202.P121.C	90202.P121.D
	≤22	1x24**	69	585x50x70	585x51	1,2	90202.P124.A	90202.P124.C	90202.P124.D
	≤22	1x28	68	1185x50x70	1185x51	2	90202.P128.A	90202.P128.C	90202.P128.D
	≤22	1x35	65	1485x50x70	1485x51	2,5	90202.P135.A	90202.P135.C	90202.P135.D
	≤22	1x39	62	885x50x70	885x51	1,6	90202.P139.A	90202.P139.C	90202.P139.D
	≤22	1x49	70	1485x50x70	1485x51	2,5	90202.P149.A	90202.P149.C	90202.P149.D
	≤25	1x54	65	1185x50x70	1185x51	2	90202.P154.A	90202.P154.C	90202.P154.D
	≤25	1x80	72	1485x50x70	1485x51	2,5	90202.P180.A	90202.P180.C	90202.P180.D

Add suffix to order:  Start - 00000.0000.0.0049  End - 00000.0000.0.0050

BLINE - Opal polycarbonate diffuser (middle) | T0 (Trimless version)

LAMP*	UGR	W	η.(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
	≤19	1x14**	42	585x50x70	585x51	1,2	90196.P114.A	90196.P114.C	90196.P114.D
	≤19	1x21	40	885x50x70	885x51	1,6	90196.P121.A	90196.P121.C	90196.P121.D
	≤22	1x24**	44	585x50x70	585x51	1,2	90196.P124.A	90196.P124.C	90196.P124.D
	≤22	1x28	55	1185x50x70	1185x51	2	90196.P128.A	90196.P128.C	90196.P128.D
	≤22	1x35	51	1485x50x70	1485x51	2,5	90196.P135.A	90196.P135.C	90196.P135.D
	≤22	1x39	36	885x50x70	885x51	1,6	90196.P139.A	90196.P139.C	90196.P139.D
	≤22	1x49	44	1485x50x70	1485x51	2,5	90196.P149.A	90196.P149.C	90196.P149.D
	≤22	1x54	44	1185x50x70	1185x51	2	90196.P154.A	90196.P154.C	90196.P154.D
	≤22	1x80	47	1485x50x70	1485x51	2,5	90196.P180.A	90196.P180.C	90196.P180.D

Add suffix to order:  Start - 00000.0000.0.0049  End - 00000.0000.0.0050

Please note:

To complete a line, Start kit will be necessary. Please order separately.
 Recessed dimensions without end caps, add 6mm to complete the line.
 **14/24W version only available as end part of the line.

*Lamp not included.



Example code for order: 90202.P180.D.0049 (START) + (3x) 90202.P180.D (MIDDLE) + 90202.P180.D.0050 (END) + 920600 + (4x) 9465 + (4x) 965100 + (4x) 930200 (OPTIONS)

We reserve the right to make technical changes without prior notice.
 Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)


OPTIONS

Start kit		Order code	Through-wiring		Order code
	Start kit	920600		1,5 mm2 through-wiring	
	• Two end caps, includes screws.			3 x 1,5 mm2	9462
				5 x 1,5 mm2	9463
				2,5 mm2 through-wiring	
				3 x 2,5 mm2	9464
				5 x 2,5 mm2	9465


Connectors

	Order code
	KIT 3-pole Mini Wieland GST15i3 (male and female) 965000
	Connector 3-pole Mini Wieland GST15i3 male 965001
	Connector 3-pole Mini Wieland GST15i3 female 965002
	KIT 5-pole Mini Wieland GST15i5 DIM (male and female) 965100
	Connector 5-pole Mini Wieland GST15i5 DIM male 965101
	Connector 5-pole Mini Wieland GST15i5 DIM female 965102


Body connector KIT

	Order code
	Body connector 930200
	• Galvanised connector, includes screws.


Light corners

	Order code
	Horizontal corner
	14W (625x625mm) 90196.H.214
	24W (625x625mm) 90196.H.224
	Vertical corner
	14W (635x635mm) 90196.V.214
	24W (635x635mm) 90196.V.224
• T5 (G5) light corner with not dimmable ballast and BLINE polycarbonate diffuser included.	


Blank parts

	Order code
	1,5m length 991100
	3m length 991101
	• Includes empty aluminium body and blanking cover.



Application type

	Order code
	T1 (Trim version) 9851
	• Additional "L" bracket.
	Please note: This option can be supplied on request.

Bespoke projects

	Please note: This option can be supplied on request.


DETAILS

	
Clip-in polycarbonate diffuser	Clip-in aluminium louvre


We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

REBA /E Line 1x80W PB
Lamp: 1 x 80W/840 HO




REBA /E Line 1x35W BLINE
Lamp: 1 x 35W/840 HE




DIMENSIONS


T0 (Trimless)



End Cap



T1 (Trim)



RECESSED DIMENSIONS

T0 (Trimless)

 For this version the cutting width is 51 mm.




T1 (Trim)

 For this version the cutting width is 65 mm.



T1 (Trim)

W	A1xB1xC1 (mm)	
1x14	585x72x74	585x65
1x21	885x72x74	885x65
1x24	585x72x74	585x65
1x28	1185x72x74	1185x65
1x35	1485x72x74	1485x65
1x39	885x72x74	885x65
1x49	1485x72x74	1485x65
1x54	1185x72x74	1185x65
1x80	1485x72x74	1485x65

Please note: Recessed dimensions without end caps, add 6mm to complete the line.

TO SPECIFY:

Trimless linear recessed T5(G5) luminaire for continuous line with 50mm width extruded aluminium profile, anodised in natural colour. Aluminium end caps and PB louvre or BLINE polycarbonate diffuser. Available with HF, DSI or DALI control gear. Optional light corners and trim version – as Indelague REBA /E Line.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.