

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: T5 (G5) lamp.


Control Gear: Electronic equipment, 220-240VAC-50/60Hz.



Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.


Fixing system: Brackets.



PB - Polished double parabolic louvre (middle) | T0 (Trimless version)

LAMP	UGR	W	η.(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
 T5	≤19	1x14**	64	585x50x70	585x51	1,2	90202.P114.A	90202.P114.C	90202.P114.D
	≤22	1x21	64	885x50x70	885x51	1,6	90202.P121.A	90202.P121.C	90202.P121.D
	≤22	1x24**	69	585x50x70	585x51	1,2	90202.P124.A	90202.P124.C	90202.P124.D
	≤22	1x28	68	1185x50x70	1185x51	2	90202.P128.A	90202.P128.C	90202.P128.D
	≤22	1x35	65	1485x50x70	1485x51	2,5	90202.P135.A	90202.P135.C	90202.P135.D
	≤22	1x39	62	885x50x70	885x51	1,6	90202.P139.A	90202.P139.C	90202.P139.D
	≤22	1x49	70	1485x50x70	1485x51	2,5	90202.P149.A	90202.P149.C	90202.P149.D
	≤25	1x54	65	1185x50x70	1185x51	2	90202.P154.A	90202.P154.C	90202.P154.D
	≤25	1x80	72	1485x50x70	1485x51	2,5	90202.P180.A	90202.P180.C	90202.P180.D

Add suffix to order:  Start - 00000.0000.0.0049  End - 00000.0000.0.0050

BLINE - Opal polycarbonate diffuser (middle) | T0 (Trimless version)

LAMP*	UGR	W	η.(%)	AxBxC (mm)	f	Kg	HF	DSI	DALI
 T5	≤19	1x14**	42	585x50x70	585x51	1,2	90196.P114.A	90196.P114.C	90196.P114.D
	≤19	1x21	40	885x50x70	885x51	1,6	90196.P121.A	90196.P121.C	90196.P121.D
	≤22	1x24**	44	585x50x70	585x51	1,2	90196.P124.A	90196.P124.C	90196.P124.D
	≤22	1x28	55	1185x50x70	1185x51	2	90196.P128.A	90196.P128.C	90196.P128.D
	≤22	1x35	51	1485x50x70	1485x51	2,5	90196.P135.A	90196.P135.C	90196.P135.D
	≤22	1x39	36	885x50x70	885x51	1,6	90196.P139.A	90196.P139.C	90196.P139.D
	≤22	1x49	44	1485x50x70	1485x51	2,5	90196.P149.A	90196.P149.C	90196.P149.D
	≤22	1x54	44	1185x50x70	1185x51	2	90196.P154.A	90196.P154.C	90196.P154.D
	≤22	1x80	47	1485x50x70	1485x51	2,5	90196.P180.A	90196.P180.C	90196.P180.D

Add suffix to order:  Start - 00000.0000.0.0049  End - 00000.0000.0.0050

Please note:

To complete a line, Start kit will be necessary. Please order separately.
 Recessed dimensions without end caps, add 6mm to complete the line.
 **14/24W version only available as end part of the line.

*Lamp not included.









Example code for order: 90202.P180.D.0049 (START) + (3x) 90202.P180.D (MIDDLE) + 90202.P180.D.0050 (END) + 920600 + (4x) 9465 + (4x) 965100 + (4x) 930200 (OPTIONS)

We reserve the right to make technical changes without prior notice.
 Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

OPTIONS

Start kit		Order code	Through-wiring		Order code
	<p>Start kit</p> <ul style="list-style-type: none"> Two end caps, includes screws. 	920600		<p>1,5 mm2 through-wiring</p> <p>3 x 1,5 mm2</p> <p>5 x 1,5 mm2</p> <p>2,5 mm2 through-wiring</p> <p>3 x 2,5 mm2</p> <p>5 x 2,5 mm2</p>	<p>9462</p> <p>9463</p> <p>9464</p> <p>9465</p>
Connectors		Order code	Body connector KIT		Order code
	<p>KIT 3-pole Mini Wieland GST15i3 (male and female)</p> <p>Connector 3-pole Mini Wieland GST15i3 male</p> <p>Connector 3-pole Mini Wieland GST15i3 female</p> <p>KIT 5-pole Mini Wieland GST15i5 DIM (male and female)</p> <p>Connector 5-pole Mini Wieland GST15i5 DIM male</p> <p>Connector 5-pole Mini Wieland GST15i5 DIM female</p>	<p>965000</p> <p>965001</p> <p>965002</p> <p>965100</p> <p>965101</p> <p>965102</p>		<p>Body connector</p> <ul style="list-style-type: none"> Galvanised connector, includes screws. 	930200
Light corners		Order code	Blank parts		Order code
	<p>Horizontal corner</p> <p>14W (625x625mm)</p> <p>24W (625x625mm)</p> <p>Vertical corner</p> <p>14W (635x635mm)</p> <p>24W (635x635mm)</p>	<p>90196.H.214</p> <p>90196.H.224</p> <p>90196.V.214</p> <p>90196.V.224</p>		<p>1,5m length</p> <p>3m length</p> <ul style="list-style-type: none"> Includes empty aluminium body and blanking cover. 	<p>991100</p> <p>991101</p>
Application type		Order code	Bespoke projects		
	<p>T1 (Trim version)</p> <ul style="list-style-type: none"> Additional "L" bracket. <p>Please note: This option can be supplied on request.</p>	9851		<p>Please note: This option can be supplied on request.</p>	

DETAILS




Clip-in polycarbonate diffuser

Clip-in aluminium louvre


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

REBA /E Line 1x80W PB
Lamp: 1 x 80W/840 HQ




REBA /E Line 1x35W BLINE
Lamp: 1 x 35W/840 HE




DIMENSIONS

T0 (Trimless)



T1 (Trim)



RECESSED DIMENSIONS


T0 (Trimless)

 For this version the cutting width is 51 mm.




T1 (Trim)

 For this version the cutting width is 65 mm.



T1 (Trim)

W	A1xB1xC1 (mm)	
1x14	585x72x74	585x65
1x21	885x72x74	885x65
1x24	585x72x74	585x65
1x28	1185x72x74	1185x65
1x35	1485x72x74	1485x65
1x39	885x72x74	885x65
1x49	1485x72x74	1485x65
1x54	1185x72x74	1185x65
1x80	1485x72x74	1485x65

Please note: Recessed dimensions without end caps, add 6mm to complete the line.

TO SPECIFY:

Trimless linear recessed T5(G5) luminaire for continuous line with 50mm width extruded aluminium profile, anodised in natural colour. Aluminium end caps and PB louvre or BLINE polycarbonate diffuser. Available with HF, DSI or DALI control gear. Optional light corners and trim version – as Roxo Lighting REBA /E Line.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.