



Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** Direct/Indirect.

**Light Source:** T5 (G5) lamp.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium profile.

**Surface Finish:** Anodised in natural colour.

PB - Polished double parabolic louvre | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x21	1191x50x140	4,2	90211.P128.A	90211.P128.C	90211.P128.D
		1x35 + 1x28	1491x50x140	5,2	90211.P135.A	90211.P135.C	90211.P135.D
		1x49 + 1x28	1491x50x140	5,2	90211.P149.A	90211.P149.C	90211.P149.D
		1x54 + 1x39	1191x50x140	4,2	90211.P154.A	90211.P154.C	90211.P154.D
		1x80 + 1x54	1491x50x140	5,2	90211.P180.A	90211.P180.C	90211.P180.D

BLINE - Opal polycarbonate diffuser | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x21	1191x50x140	4,2	90211.P128.A	90211.P128.C	90211.P128.D
		1x35 + 1x28	1491x50x140	5,2	90211.P135.A	90211.P135.C	90211.P135.D
		1x49 + 1x28	1491x50x140	5,2	90211.P149.A	90211.P149.C	90211.P149.D
		1x54 + 1x39	1191x50x140	4,2	90211.P154.A	90211.P154.C	90211.P154.D
		1x80 + 1x54	1491x50x140	5,2	90211.P180.A	90211.P180.C	90211.P180.D

DAM - Microprismatic diffuser | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x21	1191x50x140	4,2	90201.P128.A	90201.P128.C	90201.P128.D
		1x35 + 1x28	1491x50x140	5,2	90201.P135.A	90201.P135.C	90201.P135.D
		1x49 + 1x28	1491x50x140	5,2	90201.P149.A	90201.P149.C	90201.P149.D
		1x54 + 1x39	1191x50x140	4,2	90201.P154.A	90201.P154.C	90201.P154.D
		1x80 + 1x54	1491x50x140	5,2	90201.P180.A	90201.P180.C	90201.P180.D

\* Lamp not included.

Example code for order: 90201.P149.D (DALI) + 910401 + 940500 + 970002 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

### OPTIONS

#### Suspension



Suspension Type "I" (x2)

Order code  
**910401**

#### Current supply cable



1,5 m transparent current cable 0,75 mm<sup>2</sup>  
3 x 0,75 mm<sup>2</sup>  
5 x 0,75 mm<sup>2</sup>  
1,5 m transparent current cable 1,5 mm<sup>2</sup>  
3 x 1,5 mm<sup>2</sup>  
5 x 1,5 mm<sup>2</sup>

Order code

**940400**

**940500**

**940300**

**940000**

#### Ceiling rose



Colour of ceiling rose

Grey  
White  
Black

Order code

**970002**


**970000**

**970001**

### DETAILS



Suspension detail




Clip-in polycarbonate diffuser



Clip-in aluminium louvre

### DIMENSIONS



#### TO SPECIFY:

Suspended direct/indirect T5(G5) luminaire, individually mounted in extruded aluminium profile and anodised in natural colour. Aluminium end caps and PB louvre, BLINE polycarbonate or DAM microprismatic diffuser. Available with HF, DSI or DALI control gear. Optional suspensions and ceiling rose – as Roxo Lighting REBA H.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.