

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** T5 (G5) lamp.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium profile.

**Surface Finish:** Anodised in natural colour.

PB - Polished double parabolic louvre (middle)

LAMP*	UGR	W	η(%)	AxBxC (mm)	Kg	HF	DSI	DALI
T5	≤19	1x14**	64	585x50x70	1,2	90207.P114.A	90207.P114.C	90207.P114.D
	≤22	1x21	64	885x50x70	1,6	90207.P121.A	90207.P121.C	90207.P121.D
	≤22	1x24**	69	585x50x70	1,2	90207.P124.A	90207.P124.C	90207.P124.D
	≤22	1x28	68	1185x50x70	2	90207.P128.A	90207.P128.C	90207.P128.D
	≤22	1x35	65	1485x50x70	2,5	90207.P135.A	90207.P135.C	90207.P135.D
	≤22	1x39	62	885x50x70	1,6	90207.P139.A	90207.P139.C	90207.P139.D
	≤22	1x49	70	1485x50x70	2,5	90207.P149.A	90207.P149.C	90207.P149.D
	≤25	1x54	65	1185x50x70	2	90207.P154.A	90207.P154.C	90207.P154.D
	≤25	1x80	72	1485x50x70	2,5	90207.P180.A	90207.P180.C	90207.P180.D

Add suffix to order: Start - 0000.0000.0.0049 End - 0000.0000.0.0050

BLINE - Opal polycarbonate diffuser (middle)

LAMP*	UGR	W	η(%)	AxBxC (mm)	Kg	HF	DSI	DALI
T5	≤19	1x14**	42	585x50x70	1,2	90194.P114.A	90194.P114.C	90194.P114.D
	≤19	1x21	40	885x50x70	1,6	90194.P121.A	90194.P121.C	90194.P121.D
	≤22	1x24**	44	585x50x70	1,2	90194.P124.A	90194.P124.C	90194.P124.D
	≤22	1x28	55	1185x50x70	2	90194.P128.A	90194.P128.C	90194.P128.D
	≤22	1x35	51	1485x50x70	2,5	90194.P135.A	90194.P135.C	90194.P135.D
	≤22	1x39	36	885x50x70	1,6	90194.P139.A	90194.P139.C	90194.P139.D
	≤22	1x49	44	1485x50x70	2,5	90194.P149.A	90194.P149.C	90194.P149.D
	≤22	1x54	44	1185x50x70	2	90194.P154.A	90194.P154.C	90194.P154.D
	≤22	1x80	47	1485x50x70	2,5	90194.P180.A	90194.P180.C	90194.P180.D

Add suffix to order: Start - 0000.0000.0.0049 End - 0000.0000.0.0050

Please note:  
To complete a line, Start kit will be necessary. Please order separately.  
Dimensions without end caps, add 6mm to complete the line.  
\*\*14/24W version only available as end part of the line.











\* Lamp not included.  
Example code for order: 90207.P149.D.0049 (START) + 90207.P149.D (MIDDLE) + 90207.P124.D.0050 (END) + 920600 + (2x) 9463 + (2x) 965100 + (2x) 930200 + (3x) 910401 + 940500 + 970002 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

### COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

### OPTIONS

Start kit		Order code	Through-wiring		Order code
	Start kit	<b>920600</b>		1,5 mm2 through-wiring	
	• Two end caps, includes screws.			3 x 1,5 mm2	<b>9462</b>
		5 x 1,5 mm2		<b>9463</b>	
		2,5 mm2 through-wiring			
		3 x 2,5 mm2		<b>9464</b>	
		5 x 2,5 mm2		<b>9465</b>	
Connectors		Order code	Body connector KIT		Order code
	KIT 3-pole Mini Wieland GST15i3 (male and female)	<b>965000</b>		Body connector	<b>930200</b>
	Connector 3-pole Mini Wieland GST15i3 male	<b>965001</b>		• Galvanised connector, includes screws.	
	Connector 3-pole Mini Wieland GST15i3 female	<b>965002</b>			
	KIT 5-pole Mini Wieland GST15i5 DIM (male and female)	<b>965100</b>			
	Connector 5-pole Mini Wieland GST15i5 DIM male	<b>965101</b>			
	Connector 5-pole Mini Wieland GST15i5 DIM female	<b>965102</b>			
Light corners		Order code	Suspension		Order code
	Horizontal corner			Suspension Type "I" (x2)	<b>910401</b>
	14w (625x625mm)	<b>90194.H214</b>		Suspension Type "I" (x1)	<b>910400</b>
	24w (625x625mm)	<b>90194.H224</b>			
	Vertical corner				
	14w (635x635mm)	<b>90194.V214</b>			
	24w (635x635mm)	<b>90194.V224</b>			
• T5 (G5) light corner with not dimmable ballast and BLINE polycarbonate diffuser included.					
Current supply cable		Order code	Ceiling rose		Order code
	1,5 m transparent current cable 0,75 mm2			Colour of ceiling rose	
	3 x 0,75 mm2	<b>940400</b>		Grey	<b>970002</b>
	5 x 0,75 mm2	<b>940500</b>		White	<b>970000</b>
	1,5 m transparent current cable 1,5 mm2			Black	<b>970001</b>
	3 x 1,5 mm2	<b>940300</b>			
	5 x 1,5 mm2	<b>940000</b>			
Blank parts		Order code	Bespoke projects		
	1,5m length	<b>991100</b>		Please note:	
	3m length	<b>991101</b>		This option can be supplied on request.	
• Includes empty aluminium body and blanking cover.					

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### DETAILS



Suspended version



Clip-in polycarbonate diffuser




Clip-in aluminium louvre

### PHOTOMETRY


#### REBA Line 1x35W BLINE

Lamp: 1 x 35W/840 HE





#### REBA Line 1x80W PB

Lamp: 1 x 80W/840 HO



### DIMENSIONS



### TO SPECIFY:

Surface mounted or suspended linear T5(G5) luminaire for continuous line with 50mm width extruded aluminium profile, anodised in natural colour. Aluminium end caps and PB louvre or BLINE polycarbonate diffuser. Available with HF, DSI or DALI control gear. Optional light corners, suspensions and ceiling rose – as Roxo Lighting REBA Line.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.