

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wal Mounted.

Light Distribution: Direct.

Light Source: T5 (G5) lamp.


Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.



BLINE - Opal polycarbonate diffuser

LAMP*	W	η(%)	AxBxC (mm)	Kg	HF	DSI	DALI
	1x14	42	591x50x70	1,2	90178.P114.A	90178.P114.C	90178.P114.D
	1x21	40	891x50x70	1,6	90178.P121.A	90178.P121.C	90178.P121.D
	1x24	44	591x50x70	1,2	90178.P124.A	90178.P124.C	90178.P124.D
	1x28	55	1191x50x70	2	90178.P128.A	90178.P128.C	90178.P128.D
	1x35	51	1491x50x70	2,5	90178.P135.A	90178.P135.C	90178.P135.D
	1x39	36	891x50x70	1,6	90178.P139.A	90178.P139.C	90178.P139.D
	1x49	44	1491x50x70	2,5	90178.P149.A	90178.P149.C	90178.P149.D
	1x54	44	1191x50x70	2	90178.P154.A	90178.P154.C	90178.P154.D
	1x80	47	1491x50x70	2,5	90178.P180.A	90178.P180.C	90178.P180.D

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

OPTIONS

Code	Description
--	Lamps as optional.

DETAILS



Clip-in polycarbonate diffuser


* Lamp not included.

Example code for order: 90178.P128.D (DALI) + W (COLOUR/FINISH)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

REBA /P 1x28W BLINE
1 x 28W/840 HE



DIMENSIONS



TO SPECIFY:

Wall mounted direct or indirect T5(G5) aluminium profile luminaire with BLINE opal polycarbonate diffuser. Optional dimmable versions - as Roxo Lighting REBA /P.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.