



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface/Suspended.

Light Distribution: Direct.


Light Source: T5 (G5) lamp.

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.


Materials: Body: Extruded aluminium profile.

Surface Finish: Anodised in natural colour.


PB - Polished double parabolic louvre

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x28	1191x138x70	4,7	90209.P228.A	90209.P228.C	90209.P228.D
		1x35 + 1x35	1491x138x70	5,7	90209.P235.A	90209.P235.C	90209.P235.D
		1x49 + 1x49	1491x138x70	5,7	90209.P249.A	90209.P249.C	90209.P249.D
		1x54 + 1x54	1191x138x70	4,7	90209.P254.A	90209.P254.C	90209.P254.D
		1x80 + 1x80	1491x138x70	5,7	90209.P280.A	90209.P280.C	90209.P280.D

BLINE - Opal polycarbonate diffuser

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x28	1191x138x70	4,7	90047.P228.A	90047.P228.C	90047.P228.D
		1x35 + 1x35	1491x138x70	5,7	90047.P235.A	90047.P235.C	90047.P235.D
		1x49 + 1x49	1491x138x70	5,7	90047.P249.A	90047.P249.C	90047.P249.D
		1x54 + 1x54	1191x138x70	4,7	90047.P254.A	90047.P254.C	90047.P254.D
		1x80 + 1x80	1491x138x70	5,7	90047.P280.A	90047.P280.C	90047.P280.D

DAM - Microprismatic diffuser

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI	
	T5	1x28 + 1x28	1191x138x70	4,7	90208.P228.A	90208.P228.C	90208.P228.D
		1x35 + 1x35	1491x138x70	5,7	90208.P235.A	90208.P235.C	90208.P235.D
		1x49 + 1x49	1491x138x70	5,7	90208.P249.A	90208.P249.C	90208.P249.D
		1x54 + 1x54	1191x138x70	4,7	90208.P254.A	90208.P254.C	90208.P254.D
		1x80 + 1x80	1491x138x70	5,7	90208.P280.A	90208.P280.C	90208.P280.D

* Lamp not included.

Example code for order: 90208.P249.D (DALI) + 910402 + 940500 + 970002 (OPTIONS)


We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

OPTIONS

Suspension



Suspension Type "Y" (x2)

Order code
910402

Current supply cable



1,5 m transparent current cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²
1,5 m transparent current cable 1,5 mm²
3 x 1,5 mm²
5 x 1,5 mm²

Order code

940400

940500

940300

940000

Ceiling rose



Colour of ceiling rose

Grey
White
Black

Order code

970002


970000

970001

DETAILS



Suspended version



Clip-in polycarbonate diffuser



Clip-in aluminium louvre

DIMENSIONS



TO SPECIFY:

Suspended parallel T5(G5) luminaire, individually mounted in extruded aluminium profile and anodised in natural colour. Aluminium end caps and PB louvre, BLINE polycarbonate or DAM microprismatic diffuser. Available with HF, DSI or DALI control gear. Optional suspensions and ceiling rose – as Indelague REBA X.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.