



Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** T5 (G5) lamp.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium profile.

**Surface Finish:** Anodised in natural colour.

#### PB - Polished double parabolic louvre

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x28	1191x138x70	4,7	90209.P228.A	90209.P228.C	90209.P228.D
	1x35 + 1x35	1491x138x70	5,7	90209.P235.A	90209.P235.C	90209.P235.D
	1x49 + 1x49	1491x138x70	5,7	90209.P249.A	90209.P249.C	90209.P249.D
	1x54 + 1x54	1191x138x70	4,7	90209.P254.A	90209.P254.C	90209.P254.D
	1x80 + 1x80	1491x138x70	5,7	90209.P280.A	90209.P280.C	90209.P280.D

#### BLINE - Opal polycarbonate diffuser

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x28	1191x138x70	4,7	90047.P228.A	90047.P228.C	90047.P228.D
	1x35 + 1x35	1491x138x70	5,7	90047.P235.A	90047.P235.C	90047.P235.D
	1x49 + 1x49	1491x138x70	5,7	90047.P249.A	90047.P249.C	90047.P249.D
	1x54 + 1x54	1191x138x70	4,7	90047.P254.A	90047.P254.C	90047.P254.D
	1x80 + 1x80	1491x138x70	5,7	90047.P280.A	90047.P280.C	90047.P280.D

#### DAM - Microprismatic diffuser

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x28	1191x138x70	4,7	90208.P228.A	90208.P228.C	90208.P228.D
	1x35 + 1x35	1491x138x70	5,7	90208.P235.A	90208.P235.C	90208.P235.D
	1x49 + 1x49	1491x138x70	5,7	90208.P249.A	90208.P249.C	90208.P249.D
	1x54 + 1x54	1191x138x70	4,7	90208.P254.A	90208.P254.C	90208.P254.D
	1x80 + 1x80	1491x138x70	5,7	90208.P280.A	90208.P280.C	90208.P280.D

\* Lamp not included.  
Example code for order: 90208.P249.D (DALI) + 910402 + 940500 + 970002 (OPTIONS)


We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

### COLOUR / FINISH


Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)

### OPTIONS


#### Suspension

	Order code
 Suspension Type "Y" (x2)	<b>910402</b>

#### Current supply cable

	Order code
 1,5 m transparent current cable 0,75 mm <sup>2</sup> 3 x 0,75 mm <sup>2</sup> 5 x 0,75 mm <sup>2</sup>	<b>940400</b> <b>940500</b>
1,5 m transparent current cable 1,5 mm <sup>2</sup> 3 x 1,5 mm <sup>2</sup> 5 x 1,5 mm <sup>2</sup>	<b>940300</b> <b>940000</b>

#### Ceiling rose

	Order code
 Colour of ceiling rose Grey	<b>970002</b>
White	<b>970000</b>
Black	<b>970001</b>

### DETAILS



Suspended version

Clip-in polycarbonate diffuser

Clip-in aluminium louvre

### DIMENSIONS



#### TO SPECIFY:

Suspended parallel T5(G5) luminaire, individually mounted in extruded aluminium profile and anodised in natural colour. Aluminium end caps and PB louvre, BLINE polycarbonate or DAM microprismatic diffuser. Available with HF, DSI or DALI control gear. Optional suspensions and ceiling rose – as Roxo Lighting REBA X.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.