



**LED**

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface/Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium profile.

**Surface Finish:** Anodised in natural colour.

#### bGLARE - Microprismatic polycarbonate diffuser



LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	48	6078	76	60	848x120x70	4,5	90138.L230.E	90138.L230.H
	60	8104	82	61	1128x120x70	5,5	90138.L240.E	90138.L240.H
	74	10130	83	60	1408x120x70	6,5	90138.L250.E	90138.L250.H

#### bLINE - Opal polycarbonate diffuser



LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	Kg	HF	DALI
	60	7740	75	58	848x120x70	4,5	90047.L230.E	90047.L230.H
	78	10320	78	59	1128x120x70	5,5	90047.L240.E	90047.L240.H
	94	12900	80	58	1408x120x70	6,5	90047.L250.E	90047.L250.H


bGLARE | bLINE:

• To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

#### COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

#### DIMENSIONS




Example code for order: 90047.L240.H (DALI) + 3000 + 910402 + 940500 + 971400 (OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature



3000K  
Tunable white

Order code  
**3000**  
**T000**

#### Ceiling rose




Square ceiling rose  
Surface mounted  
Recessed

Order code  
**9717**  
**9714**

• To complete this option,  
please add ceiling rose colour.

#### Current supply cable



1,5 m transparent current cable 0,75 mm<sup>2</sup>  
3 x 0,75 mm<sup>2</sup>  
5 x 0,75 mm<sup>2</sup>

Order code  
**940400**  
**940500**

#### Suspension



Suspension Type "Y" (x2)


Order code  
**910402**

#### Low power option



Option supplied under request.

### DETAILS



Clip-in diffuser system



Suspension detail



End caps without visible screws

#### TO SPECIFY:

Double parallel linear suspended LED luminaire, individually mounted. Extruded aluminium profile, anodised in natural colour. Polycarbonate end caps without visible screws and polycarbonate bLINE or bGLARE diffuser. Standard version with 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta25 C). Optional DALI dimmable driver and 3000K or TunableWhite technology. Suspension kit, current supply cable and ceiling rose as accessories. – as Roxo Lighting REBA X LED.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.