



Norms: EN 60598-1, EN 60598-2-1



## PRODUCT DESCRIPTION

**Areas of Application:** Storehouses, Industrial areas, Corridors, Garages, Basements.

**Mounting:** Surface/Wall Mounted.

**Light Distribution:** Direct.

**Control Gear:** Electronic equipment, 220-240VAC-50/60Hz.

**Materials:** Body: Polyester reinforced with fiberglass. Gasket: Polyurethane, poured in one piece.

**Surface Finish:** Grey polyester RAL 7035.

LAMP*	Symbol	W	AxBxC (mm)	B1 (mm)	Kg	HF	DALI
T5	G5	1x14	623x70x125	--	1,2	9C0T.114.90.A4	9C0T.114.90.74
	G5	1x24	623x70x125	--	1,2	9C0T.124.90.A4	9C0T.124.90.74
	G5	1x28	1223x70x125	--	1,8	9C0T.128.90.A4	9C0T.128.90.74
	G5	1x35	1523x70x125	--	2,0	9C0T.135.90.A4	9C0T.135.90.74
	G5	1x49	1523x70x125	--	2,0	9C0T.149.90.A4	9C0T.149.90.74
	G5	1x54	1223x70x125	--	1,8	9C0T.154.90.A4	9C0T.154.90.74
	G5	2x14	--	117	1,4	9C0T.214.90.A4	9C0T.214.90.74
	G5	2x24	--	117	1,4	9C0T.224.90.A4	9C0T.224.90.74
	G5	2x28	--	117	2	9C0T.228.90.A4	9C0T.228.90.74
	G5	2x35	--	117	2,2	9C0T.235.90.A4	9C0T.235.90.74
	G5	2x49	--	117	2,2	9C0T.249.90.A4	9C0T.249.90.74
	G5	2x54	--	117	2	9C0T.254.90.A4	9C0T.254.90.74
	T8	G13	1x18	663x70x125	--	1,3	9B0T.118.90.A4
G13		1x36	1273x70x125	--	1,8	9B0T.136.90.A4	9B0T.136.90.74
G13		1x58	1573x70x125	--	2,1	9B0T.158.90.A4	9B0T.158.90.74
G13		2x18	--	117	1,4	9B0T.218.90.A4	9B0T.218.90.74
G13		2x36	--	117	2	9B0T.236.90.A4	9B0T.236.90.74
G13		2x58	--	117	2,3	9B0T.258.90.A4	9B0T.258.90.74

## OPTIONS

Code	Description
TUB	Lamp protection tube.
--	Lamps as optional.

## DETAILS



Fixing brackets for ceiling mounted or suspended versions




\* Lamp not included

Example code for order: 9C0T.214.90.74 (DALI) + TUB (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**PHOTOMETRY**

**DIMENSIONS**



**TO SPECIFY:**

Moisture proof luminaire equipped with IP65 lamp holder. Version with single/twin for 14/24/28/35/49/54W T5(G5) or 18/36/58W □ T8(G13) fluorescent lamp. Body in polyester reinforced with fiberglass. Optional dimmable version - as Roxo Lighting RET.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.