


LED


Norms: EN 60598-1

CE  IP 20 IP 65 IP 68 12V DC


RIBON 4,8W

IP	COLOUR TEM	POWER	W/m	Lm/m	BEAM 	CUTTING UNIT	AxB (mm)*	CODE
20	Warm White	12V DC	4,8	300	120	50mm/3LED	8x3,1	90082.L105.0E
	Cold White	12V DC	4,8	300	120	50mm/3LED	8x3,1	90082.L105.0H
65	Warm White	12V DC	4,8	400	120	50mm/3LED	8x3,1	90084.L105.0E
	Cold White	12V DC	4,8	400	120	50mm/3LED	8x3,1	90084.L105.0H

RIBON 7,2W

IP	COLOUR TEM	POWER	W/m	Lm/m	BEAM 	CUTTING UNIT	AxB (mm)*	CODE
20	Warm White	12V DC	7,2	600	120	100mm/3LED	10x3,1	90082.L107.0E
	Cold White	12V DC	7,2	600	120	100mm/3LED	10x3,1	90082.L107.0H
65	Warm White	12V DC	7,2	550	120	100mm/3LED	10x3,1	90084.L107.0E
	Cold White	12V DC	7,2	550	120	100mm/3LED	10x3,1	90084.L107.0H

RIBON 14,4W

IP	COLOUR TEM	POWER	W/m	Lm/m	BEAM 	CUTTING UNIT	AxB (mm)*	CODE
20	Warm White	12V DC	14,4	1200	120	50mm/3LED	10x3,1	90082.L114.0E
	Cold White	12V DC	14,4	1200	120	50mm/3LED	10x3,1	90082.L114.0H
65	Warm White	12V DC	14,4	1200	120	50mm/3LED	10x3,1	90084.L114.0E
	Cold White	12V DC	14,4	1200	120	50mm/3LED	10x3,1	90084.L114.0H
	RGB	12V DC	14,4	1200	120	50mm/3LED	10x3,1	90084.L114.0J
68	Warm White	12V DC	14,4	1200	120	50mm/3LED	12x4	90083.L114.0E
	Cold White	12V DC	14,4	1200	120	50mm/3LED	12x4	90083.L114.0H

Please note: LED power supply not included. One LED power supply per 5m is recommended, please order separately.


* Max. LED Strip length 5m.
Example code for order: 90082.L105.0E (CODE) + 965700 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Code	Description
965700	LED power supply 35W / 12V.
965701	LED power supply 60W / 12V.
965702	LED power supply 100W / 12V.
965703	LED power supply 150W / 12V.

DIMENSIONS



We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.