

PHOTOMETRIC RESULTS

Name:	ROFY 60 /T D/I D1150 LIGHT+ 840 HO		
Number:	90593L115	Diameter:	1348 mm
Report:	27-10-2022	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 840 - 01	Height:	131 mm
Number:	1	Power:	137,09 W
Lamp flux:	24200,00 lm	Operator:	INDELAGUE GROUP
Date:	27/10/2022 11:27:33	Output ratio:	71,3 %


Info

LiTG-class:	A40									
UTE-class:	0,71 E									
IES-class:	49 - 80 - 96 - 100 - 71									
TM5-class:	BZ4									
Divergences in the plane through maximum intensity:						Horizontal		Vertical		
One half peak divergence:						104,5°		104,1°		
Half peak side angle (left):						-52,3°		-52,0°		
Half peak side angle (right):						52,2°		52,2°		
One tenth peak divergence:						160,5°		160,0°		
Tenth peak side angle (left):						-80,3°		-79,9°		
Tenth peak side angle (right):						80,2°		80,1°		
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

PHOTOMETRIC RESULTS

Name:	ROFY 60 / T D/I D1150 LIGHT+ 840 HO		
Number:	90593L115	Diameter:	1348 mm
Report:	27-10-2022	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 840 - 01	Height:	131 mm
Number:	1	Power:	137,09 W
Lamp flux:	24200,00 lm	Operator:	INDELAGUE GROUP
Date:	27/10/2022 11:27:33	Output ratio:	71,3 %

Polar diagram ROFY 60 / T D/I D1150 LIGHT+ 840 HO / Direct in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	ROFY 60 /T D/I D1150 LIGHT+ 840 HO			
Number:	90593L115	Diameter:	1348 mm	
Report:	27-10-2022	Length:	0 mm	
Meas.-no.:	01	Width:	0 mm	
Lamp type:	LED 840 - 01	Height:	131 mm	
Number:	1	Power:	137,09 W	
Lamp flux:	24200,00 lm	Operator:	INDELAGUE GROUP	
Date:	27/10/2022 11:27:33	Output ratio:	71,3 %	

UGR Unified Glare Ratios

Ceiling reflectance	0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance	0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension	Viewed crosswise					Viewed endwise				
2H	2H	17,3	18,9	17,7	19,3	19,6	17,4	19,0	17,7	19,3
2H	3H	18,8	20,3	19,2	20,6	21,0	18,9	20,4	19,3	20,7
2H	4H	19,5	20,9	19,9	21,2	21,6	19,5	20,9	19,9	21,3
2H	6H	20,0	21,2	20,4	21,6	22,0	20,0	21,3	20,4	21,7
2H	8H	20,1	21,3	20,5	21,7	22,1	20,2	21,4	20,6	21,8
2H	12H	20,2	21,4	20,6	21,7	22,1	20,3	21,4	20,7	21,8
4H	2H	18,0	19,4	18,4	19,8	20,1	18,1	19,4	18,4	19,8
4H	3H	19,7	20,9	20,1	21,3	21,7	19,8	20,9	20,2	21,3
4H	4H	20,5	21,6	20,9	22,0	22,4	20,6	21,6	21,0	22,0
4H	6H	21,1	22,0	21,5	22,5	22,9	21,2	22,1	21,6	22,5
4H	8H	21,3	22,2	21,8	22,6	23,1	21,4	22,2	21,8	22,7
4H	12H	21,4	22,2	21,9	22,7	23,2	21,5	22,3	22,0	22,8
8H	4H	20,8	21,7	21,3	22,1	22,6	20,9	21,7	21,3	22,2
8H	6H	21,5	22,2	22,0	22,7	23,2	21,6	22,3	22,1	22,8
8H	8H	21,8	22,5	22,3	23,0	23,5	21,9	22,6	22,4	23,1
8H	12H	22,0	22,6	22,6	23,1	23,6	22,1	22,7	22,6	23,2
12H	4H	20,8	21,7	21,3	22,1	22,6	20,9	21,7	21,4	22,1
12H	6H	21,6	22,3	22,1	22,8	23,3	21,7	22,3	22,2	22,8
12H	8H	21,9	22,5	22,5	23,0	23,5	22,0	22,6	22,5	23,1

UGR values are corrected for lamp flux of 24200 lm by 11,1

PHOTOMETRIC RESULTS

Name:	ROFY 60 /T D/I D1150 LIGHT+ 840 HO		
Number:	90593L115	Diameter:	1348 mm
Report:	27-10-2022	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 840 - 01	Height:	131 mm
Number:	1	Power:	137,09 W
Lamp flux:	24200,00 lm	Operator:	INDEL AGUE GROUP
Date:	27/10/2022 11:27:33	Output ratio:	71,3 %

Luminance [cd/m²] ROFY 60 /T D/I D1150 LIGHT+ 840 HO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	4568,58	4574,27	4577,15	4582,13	4582,25	4590,66	4590,23	4590,66	4582,25
50,00	4399,93	4401,31	4409,87	4414,73	4417,81	4420,89	4425,19	4420,89	4417,81
55,00	4220,04	4227,68	4230,34	4235,12	4243,23	4248,63	4248,57	4248,63	4243,23
60,00	4038,09	4042,15	4049,78	4059,16	4065,23	4069,74	4072,68	4069,74	4065,23
65,00	3847,80	3844,32	3853,20	3867,09	3872,27	3882,09	3883,59	3882,09	3872,27
70,00	3628,59	3635,83	3644,37	3655,81	3671,20	3683,17	3687,14	3683,17	3671,20
75,00	3379,43	3395,41	3401,95	3427,63	3444,75	3446,76	3454,83	3446,76	3444,75
80,00	3061,68	3075,21	3093,67	3109,43	3132,40	3146,36	3153,58	3146,36	3132,40
85,00	2495,48	2502,83	2516,69	2552,55	2566,38	2571,24	2576,10	2571,24	2566,38

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	4582,13	4577,15	4574,27	4568,58	4574,27	4577,15	4582,13	4582,25	4590,66
50,00	4414,73	4409,87	4401,31	4399,93	4401,31	4409,87	4414,73	4417,81	4420,89
55,00	4235,12	4230,34	4227,68	4220,04	4227,68	4230,34	4235,12	4243,23	4248,63
60,00	4059,16	4049,78	4042,15	4038,09	4042,15	4049,78	4059,16	4065,23	4069,74
65,00	3867,09	3853,20	3844,32	3847,80	3844,32	3853,20	3867,09	3872,27	3882,09
70,00	3655,81	3644,37	3635,83	3628,59	3635,83	3644,37	3655,81	3671,20	3683,17
75,00	3427,63	3401,95	3395,41	3379,43	3395,41	3401,95	3427,63	3444,75	3446,76
80,00	3109,43	3093,67	3075,21	3061,68	3075,21	3093,67	3109,43	3132,40	3146,36
85,00	2552,55	2516,69	2502,83	2495,48	2502,83	2516,69	2552,55	2566,38	2571,24

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	4590,23	4590,66	4582,25	4582,13	4577,15	4574,27
50,00	4425,19	4420,89	4417,81	4414,73	4409,87	4401,31
55,00	4248,57	4248,63	4243,23	4235,12	4230,34	4227,68
60,00	4072,68	4069,74	4065,23	4059,16	4049,78	4042,15
65,00	3883,59	3882,09	3872,27	3867,09	3853,20	3844,32
70,00	3687,14	3683,17	3671,20	3655,81	3644,37	3635,83
75,00	3454,83	3446,76	3444,75	3427,63	3401,95	3395,41
80,00	3153,58	3146,36	3132,40	3109,43	3093,67	3075,21
85,00	2576,10	2571,24	2566,38	2552,55	2516,69	2502,83