

## PHOTOMETRIC RESULTS

<b>Name:</b>	ROFY 85 /E D0600 LIGHT+ 840 HO		
<b>Number:</b>	90621L600	<b>Diameter:</b>	600 mm
<b>Report:</b>	11-12-2020	<b>Length:</b>	0 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	0 mm
<b>Lamp type:</b>	LED 840 - 01	<b>Height:</b>	92 mm
<b>Number:</b>	1	<b>Power:</b>	43,96 W
<b>Lamp flux:</b>	7640,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	11/12/2020 16:10:59	<b>Output ratio:</b>	80,7 %


## Info

LiTG-class:	A40									
UTE-class:	0,81 E									
IES-class:	48 - 80 - 96 - 100 - 81									
TM5-class:	BZ4									
Divergences in the plane through maximum intensity:						Horizontal		Vertical		
One half peak divergence:						106,8°		106,9°		
Half peak side angle (left):						-53,4°		-53,4°		
Half peak side angle (right):						53,4°		53,4°		
One tenth peak divergence:						160,2°		160,0°		
Tenth peak side angle (left):						-80,1°		-80,0°		
Tenth peak side angle (right):						80,1°		80,0°		
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

## PHOTOMETRIC RESULTS

<b>Name:</b>	ROFY 85 /E D0600 LIGHT+ 840 HO		
<b>Number:</b>	90621L600	<b>Diameter:</b>	600 mm
<b>Report:</b>	11-12-2020	<b>Length:</b>	0 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	0 mm
<b>Lamp type:</b>	LED 840 - 01	<b>Height:</b>	92 mm
<b>Number:</b>	1	<b>Power:</b>	43,96 W
<b>Lamp flux:</b>	7640,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	11/12/2020 16:10:59	<b>Output ratio:</b>	80,7 %

Polar diagram ROFY 85 /E D0600 LIGHT+ 840 HO / Direct in 15° C / 5° G



## PHOTOMETRIC RESULTS

<b>Name:</b>	ROFY 85 /E D0600 LIGHT+ 840 HO			
<b>Number:</b>	90621L600	<b>Diameter:</b>	600 mm	
<b>Report:</b>	11-12-2020	<b>Length:</b>	0 mm	
<b>Meas.-no.:</b>	01	<b>Width:</b>	0 mm	
<b>Lamp type:</b>	LED 840 - 01	<b>Height:</b>	92 mm	
<b>Number:</b>	1	<b>Power:</b>	43,96 W	
<b>Lamp flux:</b>	7640,00 lm	<b>Operator:</b>	INDELAGUE GROUP	
<b>Date:</b>	11/12/2020 16:10:59	<b>Output ratio:</b>	80,7 %	

## UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	19,5	21,1	19,8	21,4	21,7	19,5	21,1	19,8	21,4	21,7
2H	3H	21,0	22,4	21,3	22,8	23,1	21,0	22,4	21,3	22,8	23,1
2H	4H	21,6	23,0	22,0	23,3	23,7	21,6	23,0	22,0	23,3	23,7
2H	6H	22,0	23,3	22,4	23,7	24,1	22,0	23,3	22,5	23,7	24,1
2H	8H	22,1	23,4	22,6	23,8	24,2	22,2	23,4	22,6	23,8	24,2
2H	12H	22,2	23,4	22,6	23,8	24,2	22,2	23,4	22,7	23,8	24,2
4H	2H	20,2	21,6	20,6	21,9	22,3	20,2	21,6	20,6	21,9	22,3
4H	3H	21,8	23,0	22,2	23,4	23,8	21,8	23,0	22,2	23,4	23,8
4H	4H	22,6	23,7	23,0	24,1	24,5	22,6	23,7	23,0	24,1	24,5
4H	6H	23,1	24,1	23,6	24,5	25,0	23,1	24,1	23,6	24,5	25,0
4H	8H	23,3	24,2	23,8	24,6	25,1	23,3	24,2	23,8	24,7	25,1
4H	12H	23,5	24,3	24,0	24,7	25,2	23,5	24,3	24,0	24,8	25,3
8H	4H	22,9	23,8	23,3	24,2	24,7	22,9	23,8	23,4	24,2	24,7
8H	6H	23,5	24,3	24,0	24,7	25,2	23,5	24,3	24,0	24,7	25,2
8H	8H	23,9	24,5	24,4	25,0	25,5	23,9	24,5	24,4	25,0	25,5
8H	12H	24,1	24,6	24,6	25,1	25,6	24,1	24,6	24,6	25,1	25,6
12H	4H	22,9	23,7	23,4	24,2	24,7	22,9	23,7	23,4	24,2	24,7
12H	6H	23,6	24,3	24,2	24,8	25,3	23,7	24,3	24,2	24,8	25,3
12H	8H	24,0	24,5	24,5	25,0	25,5	24,0	24,5	24,5	25,0	25,5

UGR values are corrected for lamp flux of 7640 lm by 7,1

## PHOTOMETRIC RESULTS

<b>Name:</b>	ROFY 85 /E D0600 LIGHT+ 840 HO		
<b>Number:</b>	90621L600	<b>Diameter:</b>	600 mm
<b>Report:</b>	11-12-2020	<b>Length:</b>	0 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	0 mm
<b>Lamp type:</b>	LED 840 - 01	<b>Height:</b>	92 mm
<b>Number:</b>	1	<b>Power:</b>	43,96 W
<b>Lamp flux:</b>	7640,00 lm	<b>Operator:</b>	INDEL AGUE GROUP
<b>Date:</b>	11/12/2020 16:10:59	<b>Output ratio:</b>	80,7 %

Luminance [cd/m<sup>2</sup>] ROFY 85 /E D0600 LIGHT+ 840 HO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	8211,69	8226,52	8221,34	8213,43	8221,84	8211,20	8208,73	8211,20	8221,84
50,00	7976,26	7981,69	7989,65	7979,86	7987,71	7979,74	7965,83	7979,74	7987,71
55,00	7700,41	7719,91	7713,65	7724,62	7719,64	7708,83	7700,18	7708,83	7719,64
60,00	7396,25	7397,64	7407,98	7398,19	7404,62	7391,48	7389,51	7391,48	7404,62
65,00	7003,71	7008,67	7030,05	7038,32	7023,89	7024,02	7014,56	7024,02	7023,89
70,00	6548,87	6555,00	6568,19	6576,37	6564,04	6575,38	6561,00	6575,38	6564,04
75,00	6007,09	5980,08	6015,21	6036,83	6030,54	6025,11	6043,15	6025,11	6030,54
80,00	5354,36	5306,04	5364,83	5352,75	5386,59	5384,16	5389,81	5384,16	5386,59
85,00	4652,19	4604,07	4670,35	4614,17	4687,81	4645,57	4638,95	4645,57	4687,81

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	8213,43	8221,34	8226,52	8211,69	8226,52	8221,34	8213,43	8221,84	8211,20
50,00	7979,86	7989,65	7981,69	7976,26	7981,69	7989,65	7979,86	7987,71	7979,74
55,00	7724,62	7713,65	7719,91	7700,41	7719,91	7713,65	7724,62	7719,64	7708,83
60,00	7398,19	7407,98	7397,64	7396,25	7397,64	7407,98	7398,19	7404,62	7391,48
65,00	7038,32	7030,05	7008,67	7003,71	7008,67	7030,05	7038,32	7023,89	7024,02
70,00	6576,37	6568,19	6555,00	6548,87	6555,00	6568,19	6576,37	6564,04	6575,38
75,00	6036,83	6015,21	5980,08	6007,09	5980,08	6015,21	6036,83	6030,54	6025,11
80,00	5352,75	5364,83	5306,04	5354,36	5306,04	5364,83	5352,75	5386,59	5384,16
85,00	4614,17	4670,35	4604,07	4652,19	4604,07	4670,35	4614,17	4687,81	4645,57

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	8208,73	8211,20	8221,84	8213,43	8221,34	8226,52
50,00	7965,83	7979,74	7987,71	7979,86	7989,65	7981,69
55,00	7700,18	7708,83	7719,64	7724,62	7713,65	7719,91
60,00	7389,51	7391,48	7404,62	7398,19	7407,98	7397,64
65,00	7014,56	7024,02	7023,89	7038,32	7030,05	7008,67
70,00	6561,00	6575,38	6564,04	6576,37	6568,19	6555,00
75,00	6043,15	6025,11	6030,54	6036,83	6015,21	5980,08
80,00	5389,81	5384,16	5386,59	5352,75	5364,83	5306,04
85,00	4638,95	4645,57	4687,81	4614,17	4670,35	4604,07