

PHOTOMETRIC RESULTS

Name:	ROFY 85 /E D0600 GCONTROL+ 830 LO		
Number:	90631L600	Diameter:	600 mm
Report:	11-12-2020	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 830 - 01	Height:	92 mm
Number:	1	Power:	32,95 W
Lamp flux:	4880,00 lm	Operator:	INDELAGUE GROUP
Date:	11/12/2020 15:05:28	Output ratio:	77,6 %


Info

LiTG-class:	A50										
UTE-class:	0,77 C										
IES-class:	62 - 88 - 97 - 100 - 77										
TM5-class:	BZ2/0.75/BZ3										
Divergences in the plane through maximum intensity:						Horizontal		Vertical			
One half peak divergence:						88,0°		89,0°			
Half peak side angle (left):						-46,2°		-42,1°			
Half peak side angle (right):						41,9°		46,9°			
One tenth peak divergence:						138,6°		139,0°			
Tenth peak side angle (left):						-71,7°		-67,0°			
Tenth peak side angle (right):						66,9°		72,0°			
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°	
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°	
	300,0°	315,0°	330,0°	345,0°							
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°	
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°		

PHOTOMETRIC RESULTS

Name:	ROFY 85 /E D0600 GCONTROL+ 830 LO		
Number:	90631L600	Diameter:	600 mm
Report:	11-12-2020	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 830 - 01	Height:	92 mm
Number:	1	Power:	32,95 W
Lamp flux:	4880,00 lm	Operator:	INDELAGUE GROUP
Date:	11/12/2020 15:05:28	Output ratio:	77,6 %

Polar diagram ROFY 85 /E D0600 GCONTROL+ 830 LO / Direct in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	ROFY 85 /E D0600 GCONTROL+ 830 LO			
Number:	90631L600	Diameter:	600 mm	
Report:	11-12-2020	Length:	0 mm	
Meas.-no.:	01	Width:	0 mm	
Lamp type:	LED 830 - 01	Height:	92 mm	
Number:	1	Power:	32,95 W	
Lamp flux:	4880,00 lm	Operator:	INDELAGUE GROUP	
Date:	11/12/2020 15:05:28	Output ratio:	77,6 %	

UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	15,4	16,9	15,8	17,2	17,5	15,3	16,8	15,7	17,1	17,4
2H	3H	16,1	17,4	16,4	17,7	18,1	15,9	17,3	16,3	17,6	17,9
2H	4H	16,4	17,6	16,8	18,0	18,3	16,2	17,5	16,6	17,8	18,2
2H	6H	16,7	17,8	17,1	18,2	18,6	16,5	17,7	16,9	18,0	18,4
2H	8H	16,7	17,8	17,1	18,2	18,6	16,6	17,7	17,0	18,1	18,5
2H	12H	16,8	17,8	17,2	18,2	18,6	16,6	17,7	17,0	18,1	18,5
4H	2H	15,7	16,9	16,1	17,2	17,6	15,6	16,8	16,0	17,1	17,5
4H	3H	16,5	17,5	16,9	17,9	18,3	16,3	17,4	16,8	17,8	18,2
4H	4H	16,9	17,9	17,4	18,3	18,7	16,8	17,7	17,2	18,1	18,6
4H	6H	17,3	18,1	17,8	18,5	19,0	17,2	18,0	17,6	18,4	18,9
4H	8H	17,4	18,2	17,9	18,6	19,1	17,3	18,1	17,8	18,5	19,0
4H	12H	17,5	18,2	18,0	18,7	19,2	17,4	18,1	17,9	18,6	19,1
8H	4H	17,0	17,8	17,5	18,2	18,7	16,9	17,7	17,4	18,1	18,6
8H	6H	17,5	18,1	18,0	18,6	19,1	17,4	18,0	17,9	18,5	19,0
8H	8H	17,7	18,3	18,3	18,8	19,3	17,6	18,2	18,1	18,7	19,2
8H	12H	17,9	18,4	18,4	18,9	19,4	17,8	18,2	18,3	18,7	19,3
12H	4H	17,0	17,7	17,5	18,2	18,7	16,9	17,6	17,4	18,1	18,6
12H	6H	17,6	18,1	18,1	18,6	19,1	17,4	18,0	18,0	18,5	19,0
12H	8H	17,8	18,3	18,3	18,8	19,3	17,7	18,1	18,2	18,6	19,2

UGR values are corrected for lamp flux of 4880 lm by 5,5

PHOTOMETRIC RESULTS

Name:	ROFY 85 /E D0600 GCONTROL+ 830 LO		
Number:	90631L600	Diameter:	600 mm
Report:	11-12-2020	Length:	0 mm
Meas.-no.:	01	Width:	0 mm
Lamp type:	LED 830 - 01	Height:	92 mm
Number:	1	Power:	32,95 W
Lamp flux:	4880,00 lm	Operator:	INDEL AGUE GROUP
Date:	11/12/2020 15:05:28	Output ratio:	77,6 %

Luminance [cd/m²] ROFY 85 /E D0600 GCONTROL+ 830 LO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	5239,94	4998,72	5088,77	5120,94	5022,32	4937,13	5037,80	4937,13	5022,32
50,00	3956,60	4157,67	4063,07	4034,25	3999,04	3955,23	4029,67	3955,23	3999,04
55,00	3257,05	3339,41	3146,29	3180,50	3218,61	3254,86	3257,91	3254,86	3218,61
60,00	2847,54	2604,47	2729,77	2624,88	2635,77	2639,51	2678,46	2639,51	2635,77
65,00	2357,58	2330,53	2388,68	2302,57	2266,25	2212,96	2374,14	2212,96	2266,25
70,00	2168,31	2180,27	2166,07	2166,12	2093,91	2064,08	2134,67	2064,08	2093,91
75,00	2187,28	2110,76	2102,30	2137,60	2099,22	2091,18	2056,56	2091,18	2099,22
80,00	2151,67	2202,46	2176,19	2073,74	2133,32	2170,07	2253,86	2170,07	2133,32
85,00	2273,39	2433,84	2363,44	2069,81	2226,29	2194,20	2155,48	2194,20	2226,29

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	5120,94	5088,77	4998,72	5239,94	4998,72	5088,77	5120,94	5022,32	4937,13
50,00	4034,25	4063,07	4157,67	3956,60	4157,67	4063,07	4034,25	3999,04	3955,23
55,00	3180,50	3146,29	3339,41	3257,05	3339,41	3146,29	3180,50	3218,61	3254,86
60,00	2624,88	2729,77	2604,47	2847,54	2604,47	2729,77	2624,88	2635,77	2639,51
65,00	2302,57	2388,68	2330,53	2357,58	2330,53	2388,68	2302,57	2266,25	2212,96
70,00	2166,12	2166,07	2180,27	2168,31	2180,27	2166,07	2166,12	2093,91	2064,08
75,00	2137,60	2102,30	2110,76	2187,28	2110,76	2102,30	2137,60	2099,22	2091,18
80,00	2073,74	2176,19	2202,46	2151,67	2202,46	2176,19	2073,74	2133,32	2170,07
85,00	2069,81	2363,44	2433,84	2273,39	2433,84	2363,44	2069,81	2226,29	2194,20

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	5037,80	4937,13	5022,32	5120,94	5088,77	4998,72
50,00	4029,67	3955,23	3999,04	4034,25	4063,07	4157,67
55,00	3257,91	3254,86	3218,61	3180,50	3146,29	3339,41
60,00	2678,46	2639,51	2635,77	2624,88	2729,77	2604,47
65,00	2374,14	2212,96	2266,25	2302,57	2388,68	2330,53
70,00	2134,67	2064,08	2093,91	2166,12	2166,07	2180,27
75,00	2056,56	2091,18	2099,22	2137,60	2102,30	2110,76
80,00	2253,86	2170,07	2133,32	2073,74	2176,19	2202,46
85,00	2155,48	2194,20	2226,29	2069,81	2363,44	2433,84